



HSS Dura 25 Kernebor m/ 3/4 in Weldon-holder

TiN overfladebelægning for ekstraordinære holdbarhed og nedsat friktion.

Metriske dimensioner, boreddybde 25 mm.

411,75 kr ekskl. Moms

Produktnummer: 6 31 34 290 07 5

Tekniske data

GENERELLE TEKNISKE DATA

Snitdybde

25 mm

Bor-Ø

29 mm

Passer til

Universal

- > KBU 35 Q
- > KBU 35 MQ
- > KBU 35-2 Q
- > KBU 35 QW
- > KBU 35 MQW
- > KBU 35-2 QW
- > KBU 35 PQW
- > KBU 35 PQ
- > KBM 50 U
- > KBM 50 Q
- > KBM 65 U
- > KBU 35 QW Structural Steel-Set 3/4 in Weldon
- > KBU 35 QW Fabricator M12 Tapping-Set 3/4 in Weldon
- > KBM 50 UQW
- > KBM 65 UQW
- > AKBU 35 PMQ AS
- > AKBU 35 PMQW AS
- > AKBU 35 PMQW 18 V AS-sæt 2x 8 Ah
- > AKBU 35 PMQW 18 V AS
- Set 1x 12 Ah
- > AKBU 35 PMQW AS Construction-Site-sæt 3/4 in Weldon / HSS NOVA 50
- > AKBU 35 PMQW 18 V AS Construction-Site 1x 12 Ah-sæt 3/4 in Weldon / HSS NOVA 50
- > AKBU 35 PMQW 18 V AS Construction-Site 2x 8 Ah-sæt 3/4 in Weldon / HSS NOVA 50

Endurance

- > KBE 50-2
- > KBE 32
- > KBE 32 QW
- > KBE 36 MAGSPEED
- > KBE 36 QW MAGSPEED
- > KBE 36 QW MAGSPEED
Fabrication-sæt

Automatic

- > KBM 50 auto
- > KBM 50 auto QW