



HSS Dura 25 Kernbohrer mit 3/4 in Weldon- Aufnahme

TiN Oberflächenbeschichtung für hervorragende
Standzeiten und beste Gleiteigenschaften.

Metrische Abmessungen, Schnitttiefe 25 mm.

69.66 CHF UVP + vRG inkl. MwSt.

Bestellnummer: 6 31 34 290 07 5

Technische Daten

ALLGEMEINE TECHNISCHE DATEN

Schnitttiefe

25 mm

Bohr-Ø

29 mm

Passend für folgende Maschinen

Universal

- > KBM 50 U
- > KBM 50 Q
- > KBM 65 U
- > KBU 35 Q
- > KBU 35 MQ
- > KBU 35 PQ
- > KBU 35-2 Q
- > KBU 35 MQW
- > KBU 35-2 QW
- > KBU 35 PQW
- > KBU 35 QW
- > KBU 35 QW Fabricator M12 Tapping-Set 3/4 in Weldon
- > KBM 50 UQW
- > KBM 65 UQW
- > KBU 35 QW Structural Steel-Set 3/4 in Weldon
- > AKBU 35 PMQ AS
- > AKBU 35 PMQW AS
- > AKBU 35 PMQW 18 V AS Set 2x 8 Ah
- > AKBU 35 PMQW 18 V AS Set 1x 12 Ah
- > AKBU 35 PMQW AS Construction-Site Set 3/4 in Weldon / HSS NOVA 50
- > AKBU 35 PMQW 18 V AS Construction-Site 1x 12 Ah Set 3/4 in Weldon / HSS NOVA 50
- > AKBU 35 PMQW 18 V AS Construction-Site 2x 8 Ah Set 3/4 in Weldon / HSS NOVA 50

Endurance

- > KBE 50-2
- > KBE 32 QW
- > KBE 36 MAGSPEED
- > KBE 36 QW MAGSPEED
- > KBE 36 QW MAGSPEED Fabrication Set

Automatic

- > KBM 50 auto
- > KBM 50 auto QW