



HSS Dura 25 core bit with QuickIN holder

TiN surface coating for outstanding service lives and the best glide properties.

Metric dimensions, cutting depth 25 mm.

Product number: 6 31 33 190 06 7

Technical data

TECHNICAL DATA

Cutting depth

25 mm

Bore Ø

19 mm

Suitable for the following tools

Universal

- > KBM 65 U
- > KBM 50 Q
- > KBM 50 UQW
- > KBM 65 UQW
- > KBM 50 U
- > KBU 35 QW Fabricator M12 Tapping-Set 3/4 in Weldon
- > KBU 35 QW Structural Steel-Set 3/4 in Weldon
- > KBU 35 PQ
- > KBU 35 PQW
- > KBU 35-2 QW
- > KBU 35 MQW
- > KBU 35 QW
- > KBU 35-2 Q
- > KBU 35 MQ
- > KBU 35 Q
- > AKBU 35 PMQW 18 V AS CONSTRUCTION SITE 2x 8 Ah set 3/4 in Weldon / HSS NOVA 50
- > AKBU 35 PMQW 18 V AS CONSTRUCTION SITE 1x
- 12 Ah set 3/4 in Weldon / HSS NOVA 50
- > AKBU 35 PMQW AS CONSTRUCTION SITE set 3/4 in Weldon / HSS NOVA 50
- > AKBU 35 PMQW 18 V AS Set 1x 12 Ah
- > AKBU 35 PMQW 18 V AS set 2x 8 Ah
- > AKBU 35 PMQW AS
- > AKBU 35 PMQ AS



Automatic

> KBM 50 auto QW

> KBM 50 auto