



WBP 10

Angle drill up to 10 mm

Extremely small angle drill for working in difficult-to-reach spots.

Product number: 7 205 51 60 00 0

Details

- + FEIN high-power motor with good speed stability for constant drilling progress in almost any application.
- + Particularly flat and slim design with 17 mm width across corners and 96 mm gearbox head height for work in tight spaces and corners.
- + Flexible and universal use thanks to clockwise and reverse running for thread cuts up to M6.
- + Metal gear head.
- + Tapered drill shaft.
- + High-precision metal drill chuck.
- + High concentricity.
- + Distortion-free barrel-type motor housing.
- + FEIN Sensitive Handle.
- + 5 metre cable.

Price includes

- + 1 3-jaw chuck up to \varnothing 10 mm
- + 1 drill chuck key

Technical data

TECHNICAL DATA

| | |
|-----------------------|---------------|
| Input | 500 W |
| Output | 270 W |
| Speed, full load | 0 - 1,030 rpm |
| Speed, no load | 0 - 1,830 rpm |
| Torque at max. output | 8 Nm |

VIBRATION AND SOUND EMISSION VALUES

| | |
|--|---------------|
| Sound pressure level LpA Uncertainty of measured value KpA | 82 dB 3 dB |
| Sound power level LWA Uncertainty of measured value KWA | 93 dB 3 dB |
| Sound peak value LpCpeak Uncertainty of measured value | 96 dB |



| | | | |
|---|-------------|---|----------------------|
| power | | KpCpeak | 3 dB |
| Stall torque | 21 Nm | Vibration value 1 α_{hv} 3-way | 3 m/s ² |
| Drill chuck clamping width | 0.8 - 10 mm | Uncertainty of measured value $K\alpha$ | 1,5 m/s ² |
| Capacity in steel \emptyset | 10 mm | | |
| capacity in \emptyset stainless steel | 10 mm | | |
| Capacity in alu \emptyset | 15 mm | | |
| Capacity in wood \emptyset | 25 mm | | |
| Tapping | M 6 | | |
| Cone at drill shaft | B 10 | | |
| Width across corners | 17 mm | | |
| Gearbox head height | 96 | | |
| Cable with plug | 5 m | | |
| Weight according to EPTA | 1.50 kg | | |
| Weight according to EPTA | 1.50 kg | | |

Application examples



FEIN

