



WBP 10

Angle drill up to 10 mm

Extremely small angle drill for working in difficult-to-reach spots.

Product number: 7 205 51 60 00 0

Details

- + FEIN high-power motor with good speed stability for constant drilling progress in almost any application.
- + Particularly flat and slim design with 17 mm width across corners and 96 mm gearbox head height for work in tight spaces and corners.
- + Flexible and universal use thanks to clockwise and reverse running for thread cuts up to M6.
- + Metal gear head.
- + Tapered drill shaft.
- + High-precision metal drill chuck.
- + High concentricity.
- + Distortion-free barrel-type motor housing.
- + FEIN Sensitive Handle.
- + 5 metre cable.

Price includes

- + 1 3-jaw chuck up to Ø 10 mm
- + 1 drill chuck key

Technical data

TECHNICAL DATA

Input	500 W
Output	270 W
Speed, full load	0 - 1,030 rpm
Speed, no load	0 - 1,830 rpm
Torque at max. output	8 Nm

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA Uncertainty of measured value KpA	82 dB 3 dB
Sound power level LWA Uncertainty of measured value KWA	93 dB 3 dB
Sound peak value LpCpeak Uncertainty of measured value	96 dB



FEIN

power		KpCpeak	3 dB
Stall torque	21 Nm	Vibration value 1 α_{hv} 3-way	3 m/s ²
Drill chuck clamping width	0.8 - 10 mm	Uncertainty of measured value K α	1,5 m/s ²
Capacity in steel Ø	10 mm		
capacity in Ø stainless steel	10 mm		
Capacity in alu Ø	15 mm		
Capacity in wood Ø	25 mm		
Tapping	M 6		
Cone at drill shaft	B 10		
Width across corners	17 mm		
Width across corners	17 mm		
Gearbox head height	96		
Cable with plug	5 m		
Weight according to EPTA	1.50 kg		

Application examples

