



# ABS 18 Q AS

## 2-speed cordless drill/driver

With brushless motor and QuickIN interface. Perfectly suited to drilling up to 13 mm and tapping up to M10.

Product number: 7 113 24 61 00 0

### Details

- + Two-speed solid metal gearbox perfectly suited to drilling up to 13 mm and tapping up to M10 in metal.
- + Enjoy the greatest versatility with the FEIN QuickIN system. Work at speed in metal and timber with just one tool.
- + QuickIN solid metal drill chuck (120 Nm) with carbide-tipped clamping jaws and high clamping forces.
- + Brushless FEIN PowerDrive motor with 30 % higher efficiency and long service life.
- + Mechanical torque setting.
- + Compact design.
- + The AMPShare interface makes almost 50% more screw connections (approx. 1300 screw connections, diameter of 5 x 40 mm in timber) possible per battery charge with the same level of FEIN quality. (ProCORE 4 Ah).
- + Bit and belt holder on the side for ergonomic and flexible handling.
- + Compatible with Bosch Professional 18 V batteries (available since 2008) and AMPShare batteries.
- + Maximum work progress with AMPShare 18V ProCORE batteries: COOLPACK 2.0 technology delivers a 135% longer battery life. State-of-the-art cell technology and intelligent battery management deliver 87% more power than with conventional batteries. "Electronic Cell Protection" (ECP) protects the battery from overload, overheating and total discharge.
- + Ideally equipped for every form of use. Mobile working with the L-BOXX system.

### Price includes

- + 1 QuickIN drill chuck (120 Nm)
- + 1 magnetic bit storage
- + 1 belt clip
- + 1 tool case (L-Boxx 136)

### Product feature

- + Removable drill chuck
- + QuickIN accessory interface

### Technical data

#### TECHNICAL DATA

#### VIBRATION AND SOUND EMISSION VALUES



Battery voltage	18 V	Sound pressure level LpA Uncertainty of measured value KpA	74,3 dB 5 dB
Battery compatibility	Li-ion / ProCORE Li-ion		
Battery interface	18 V AMPShare	Sound power level LWA Uncertainty of measured value KWA	82,3 dB 5 dB
Motor	brushless	Sound peak value	88,1 dB
Gearbox	2-speed	LpCpeak Uncertainty of measured value KpCpeak	5 dB
Accessory interface	QuickIN	Vibration value 1 $\alpha_{hv}$ 3- way	ah,D 1,1 m/s <sup>2</sup>
Speed, no load	450 / 2,000 rpm	Vibration value 2 $\alpha_{hv}$ 3-way	ah 1,2 m/s <sup>2</sup>
Max. torque (hard/soft)	60 / 38 Nm	Uncertainty of measured value K $\alpha$	1,5 m/s <sup>2</sup>
Torque levels	22 + 1		
Drill chuck clamping width	1.5 - 13 mm		
Fastening	8 x 300 mm		
Capacity in steel Ø	13 mm		
Capacity in wood Ø	50 mm		
Tapping	M 10		
Weight without storage battery	1.40 kg		

## Application examples



Powered by  **BOSCH**

**Kompatibel mit  
AMPShare- / Bosch  
Professional 18 V  
Akkus. | Compatible  
with AMPShare/Bosch**

Professional 18 V batteries. | Compatible avec  
les batteries 18 V AMPShare/Bosch Professional. |  
Compatible con baterías AMPShare/Bosch  
Professional de 18 V. | Compatibile con le batterie  
AMPShare / Bosch Professional da 18 V.

