



## ASB 18 Q AS Set 5 Ah

#### 2-speed cordless combi drill

With brushless motor and QuickIN interface. Perfectly suited to drilling up to 13 mm in metal, stone and masonry.

Product number: 7 104 07 62 00 0

#### Details

- 2-speed solid metal gearbox and switchable striking mechanism for optimum drilling in metal, stone and masonry.
- Enjoy the greatest versatility with the FEIN QuickIN system. Work at speed in metal and timber with just one tool.
- QuickIN solid metal drill chuck (120 Nm) with carbide-tipped clamping jaws and high clamping forces.
- Brushless FEIN PowerDrive motor with 30 % higher efficiency and long service life.
- + Mechanical torque setting.
- + Compact design.
- The AMPShare interface makes almost 50% more screw connections (approx. 1600 screw connections, diameter of 5 x 40 mm in timber) possible per battery charge with the same level of FEIN quality. (GBA 18 V 5 Ah).

- Bit and belt holder on the side for ergonomic and flexible handling.
- Compatible with all 18 V AMPShare ProCORE batteries and chargers for even more power and flexibility. Also suitable for 18 V Bosch Professional cordless devices.
- Compatible with Bosch Professional 18 V batteries (available since 2008) and AMPShare batteries.
- Maximum work progress with AMPShare 18V ProCORE batteries: COOLPACK 2.0 technology delivers a 135% longer battery life. State-of-theart cell technology and intelligent battery management deliver 87% more power than with conventional batteries. "Electronic Cell Protection" (ECP) protects the battery from overload, overheating and total discharge.
- Ideally equipped for every form of use. Mobile working with the L-BOXX system.

#### Price includes

- + 1 QuickIN drill chuck (120 Nm)
- + 1 magnetic bit storage
- 2 Li-Ion storage battery GBA 18V
  5.0 Ah AS
- + 1 belt clip
- + 1 tool case (L-Boxx 136)
- + 1 rapid charger GAL 1880 CV AS

- Product feature
- + Removable drill chuck
- + QuickIN accessory interface
- + Switchable impact mechanism



#### Technical data

### TECHNICAL DATA

# VIBRATION AND SOUND EMISSION VALUES

Battery voltage	18 V	Sound pressure level LpA Uncertainty of measured value KpA	92,9 dB 3 dB
Battery capacity	5 Ah	кра	
Battery compatibility	Li-ion / ProCORE Li-ion	Sound power level LWA Uncertainty of measured value KWA	100,9 dB 3 dB
Battery interface	18 V AMPShare	Sound peak value	110,0 dB
Motor	brushless	LpCpeak Uncertainty of measured value KpCpeak	3 dB
Gearbox	2-speed		
Accessory interface	QuickIN	Vibration value 1 αhv 3- way Vibration value 2 αhv 3-way	ah,D 1,4 m/s² ah 0,6 m/s²
Speed, no load	450 / 2,000 rpm	Uncertainty of measured	1,5 m/s²
Impacts	7,360 / 32,000 rpm	value K <b>a</b>	
Max. torque (hard/soft)	60 / 38 Nm		
Torque levels	22 + 1		
Drill chuck clamping width	1.5 - 13 mm		
Fastening	8 x 300 mm		
Capacity in steel Ø	13 mm		
Capacity in wood Ø	50 mm		
Capacity in stone Ø	13 mm		
Tapping	M 10		
Weight without storage battery	1.50 kg		



#### Application examples



Kompatibel mit AMPShare-/ Bosch Professional 18 V Akkus. | Compatible with AMPShare/Bosch

Professional 18 V batteries. | Compatible avec les batteries 18 V AMPShare/Bosch Professional. | Compatible con baterías AMPShare/Bosch Professional de 18 V. | Compatibile con le batterie AMPShare / Bosch Professional da 18 V.



