



# ASCD 18-1000 W34 AS Set 8 Ah ProCORE

## Cordless impact wrench/driver

Up to max. 1050 Nm with brushless motor and 6-stage torque setting. For metric screwdriving applications up to M27.

Product number: 7 115 12 62 00 0

## Details

- + For extreme precision work: The ASCD 18-1000 W34 AS with electronic torque setting (6 levels) prevents screw heads from shearing off.
- + VARIO 3/4" adapter, available as an extra and developed by FEIN. Suitable for all VARIO accessories for simple and mechanical drilling, countersinking, tapping, recutting and cleaning through threads up to a maximum of M30. Turns the impact wrench/driver into a tapper, thereby adding a whole new tool to the range of applications.
- + Brushless FEIN PowerDrive motor with 30 % higher efficiency and long service life.
- + 3/4" square head for holding sockets.
- + High torque of up to 1050 Nm for tightening and loosening screws of up to M27.
- + Maximum release torque of 1500 Nm in reverse running.
- + Robust solid metal impact gear.
- + Up to 600 screw connections (M27) with one battery charge (ProCORE 8.0 Ah).
- + Compatible with Bosch Professional 18 V batteries (available since 2008) and AMPShare batteries.
- + Maximum work progress with AMPShare 18V ProCORE batteries: COOLPACK 2.0 technology delivers a 135% longer battery life. State-of-the-art cell technology and intelligent battery management deliver 87% more power than with conventional batteries. "Electronic Cell Protection" (ECP) protects the battery from overload, overheating and total discharge.
- + Ideally equipped for every job. Mobile working with the L-BOXX system.

## Price includes

- + 1 belt clip
- + 2 ProCORE 18 V 8.0 Ah battery pack
- + 1 tool case (L-BOXX 136)
- + 1 magnetic bit storage
- + 1 x GAL18 V-160 AS rapid charger

## Technical data

### TECHNICAL DATA

## VIBRATION AND SOUND EMISSION VALUES

Battery voltage	18 V	Sound pressure level LpA Uncertainty of measured value KpA	96,7 dB 3 dB
Battery capacity	8 Ah		
Battery compatibility	Li-ion / ProCORE Li-ion	Sound power level LWA Uncertainty of measured value KWA	104,7 dB 3 dB
Battery interface	18 V AMPShare		
Motor	brushless	Sound peak value LpCpeak Uncertainty of measured value KpCpeak	121,3 dB 3 dB
Speed, no load	0 - 1 800 rpm		
Impacts	0 - 2 200 rpm	Vibration value 1 $\alpha_{hv}$ 3- way Uncertainty of measured value K $\alpha$	ah 15,7 m/s <sup>2</sup> 1,5 m/s <sup>2</sup>
Max. torque	1 050 Nm		
Torque levels	6		
Tool Holder	3/4 in Outer square		
Max. metric screw	M27 (8.8)		
Wood screw Ø	12 x 600 mm		
Weight without storage battery	3.10 kg		

## Application examples



Powered by  BOSCH

**Kompatibel mit AMPShare- / Bosch Professional 18 V Akkus.** | Compatible with AMPShare/Bosch

Professional 18 V batteries. | Compatible avec les batteries 18 V AMPShare/Bosch Professional. | Compatible con baterías AMPShare/Bosch Professional de 18 V. | Compatibile con le batterie AMPShare / Bosch Professional da 18 V.



