



# FEIN



## ASCD 18-200 W4 AS

### Cordless impact wrench/driver

Up to max. 210 Nm with brushless motor and 6-stage torque setting. For universal screwdriving applications including self-drilling screwdriving.

Product number: 7 115 11 61 00 0

### Details

- + For extreme precision work: The ASCD 18-200 W4 AS with electronic torque setting (6 levels) prevents screw heads from shearing off.
- + Brushless motor with 30% higher efficiency and long service life.
- + 1/4" hexagon socket tool mounting for holding bits and socket wrench inserts.
- + 10% more torque in reverse running to loosen screws which are extremely tight.
- + Robust solid metal impact gear.
- + Contact guard on gearbox head.
- + Compact design.
- + 700 screw connections (M18) with one battery charge (ProCORE 4 Ah).
- + Bit and belt holder on the side for ergonomic and flexible handling.
- + Compatible with Bosch Professional 18 V batteries (available since 2008) and AMPShare batteries.
- + Maximum work progress with AMPShare 18V ProCORE batteries: COOLPACK 2.0 technology delivers a 135% longer battery life. State-of-the-art cell technology and intelligent battery management deliver 87% more power than with conventional batteries. "Electronic Cell Protection" (ECP) protects the battery from overload, overheating and total discharge.
- + Ideally equipped for every form of use. Mobile working with the L-BOXX system.

### Price includes

- + 1 belt clip
- + 1 magnetic bit storage
- + 1 tool case (L-Boxx 136)

### Technical data

#### TECHNICAL DATA

Battery voltage

18 V

Battery compatibility

Li-ion / ProCORE Li-ion

#### VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA  
Uncertainty of measured value  
KpA

96,1 dB  
3 dB



# FEIN

Battery interface	18 V AMPShare	Sound power level LWA Uncertainty of measured value KWA	104,1 dB 3 dB
Motor	brushless		
Speed, no load	0 - 1 500 rpm	Sound peak value LpCpeak Uncertainty of measured value KpCpeak	118,1 dB 3 dB
Impacts	0 - 3 000 rpm		
Max. torque	210 Nm	Vibration value 1 $\alpha_{hv}$ 3- way Uncertainty of measured value K $\alpha$	$\alpha_h$ 13,4 m/s <sup>2</sup> 1,5 m/s <sup>2</sup>
Torque levels	6		
Tool Holder	1/4 in hexagon socket		
Wood screw Ø	8 x 200 mm		
Weight without storage battery	1.20 kg		

## Application examples



**Kompatibel mit  
AMPShare-/ Bosch  
Professional 18 V  
Akkus.** | Compatible  
with AMPShare/Bosch

Professional 18 V batteries. | Compatible avec  
les batteries 18 V AMPShare/Bosch Professional. |  
Compatible con baterías AMPShare/Bosch  
Professional de 18 V. | Compatibile con le batterie  
AMPShare / Bosch Professional da 18 V.





**FEIN**

