



## MBS 32 F

### Magnetic Drill Jigs

Flexible magnetic drill jig with fine adjustment for rotary drills with up to 32 mm drill capacity.

Product number: 9 03 16 223 00 8

### Details

- + Universal suitability for drilling, tapping, reaming and countersinking.
- + Fine adjustment of drill spindle for easy alignment of machine without constantly removing and refitting the magnet.
- + High magnetic holding power and safety circuit guarantee safe working in any position.
- + Infinitely variable stroke range setting.
- + Compact design.
- + Optimum power-to-weight ratio.
- + Robust and accurate dual dove-tail guide
- + Universal use for drive machines with clamping collar.

### Price includes

- + 1 clamping strap
- + 1 Chip grid
- + 1 swarf hook
- + 2 keys

### Technical data

#### TECHNICAL DATA

|                    |            |
|--------------------|------------|
| Input              | 130 W      |
| Socket max.        | 16 A       |
| For collar Ø       | 63 / 65 mm |
| Twist drill max. Ø | 32 mm      |
| Tapping            | M 24       |



|                                 |              |
|---------------------------------|--------------|
| Countersinking max. Ø           | 60 mm        |
| Reaming max. Ø                  | 40 mm        |
| Stroke                          | 178 mm       |
| Total stroke range              | 365 mm       |
| Adjustment range for drill jigs | 10 mm        |
| Swivel range for drill jigs     | 350°         |
| Magnetic holding power          | 18,000 N     |
| Magnetic foot dimensions        | 220 x 100 mm |
| Cable with plug                 | 4 m          |
| Weight according to EPTA        | 21.80 kg     |