



MBS 32 F

Magnetic Drill Jigs

Flexible magnetic drill jig with fine adjustment for rotary drills with up to 32 mm drill capacity.

Product number: 9 03 16 223 00 8

Details

- + Universal suitability for drilling, tapping, reaming and countersinking.
- + Fine adjustment of drill spindle for easy alignment of machine without constantly removing and refitting the magnet.
- + High magnetic holding power and safety circuit guarantee safe working in any position.
- + Infinitely variable stroke range setting.
- + Compact design.
- + Optimum power-to-weight ratio.
- + Robust and accurate dual dove-tail guide
- + Universal use for drive machines with clamping collar.

Price includes

- + 1 clamping strap
- + 1 swarf guard
- + 1 swarf hook
- + 2 keys

Technical data

TECHNICAL DATA

Input	130 W
Socket max.	16 A
For collar Ø	63 / 65 mm
Twist drill max. Ø	32 mm
Tapping	M 24



Countersinking max. Ø

60 mm

Reaming max. Ø

40 mm

Stroke

178 mm

Total stroke range

365 mm

Adjustment range for drill jigs

10 mm

Swivel range for drill jigs

350°

Magnetic holding power

18,000 N

Magnetic foot dimensions

220 x 100 mm

Cable with plug

4 m

Weight according to EPTA

21.80 kg