



MBS 25 F

Magnetic Drill Jigs

Flexible magnetic drill jig with fine adjustment for rotary drills with up to 23 mm drill capacity.

Product number: 9 03 22 223 00 0

Details

- + Universal suitability for drilling, tapping, reaming and countersinking.
- + Fine adjustment of the drill spindle for convenient tool alignment.
- + Double drill motor guide for use with very large drilling tools.
- + Feed handwheel can be moved from one side to the other.
- + Integrated coolant tank with flexible jointed hose.
- + High magnetic holding force.
- + Carriage height adjustable without tools.

Price includes

- + 1 coolant tank
- + 1 lashing strap
- + 1 contact guard
- + 1 reducing ring, diameter 43 mm

Technical data

TECHNICAL DATA

Input

100 W

Socket max.

16 A

For collar Ø

53 mm

Twist drill max. Ø

25 mm

Tapping

M 20



Countersinking max. Ø	50 mm
Reaming max. Ø	25 mm
Stroke	145 mm
Total stroke range	290 mm
Adjustment range for drill jigs	6 mm
Swivel range for drill jigs	7°
Magnetic holding power	14,000 N
Magnetic foot dimensions	205 x 95 mm
Cable with plug	4 m
Weight according to EPTA	12.50 kg