



BOP 10-2

Two-Speed Hand Drill up to 10 mm

Universal two-speed drill, up to 10 mm with ideal speed range for steel and stainless steel.

Product number: 7 205 54 60 00 0

Details

- + Mechanical two-speed gearbox for optimum speed adjustment for a wide range of uses.
- + FEIN high-power motor with good speed stability for constant drilling progress in almost any application.
- + Metal gear head and distortion-free barrel-type motor housing for superb service life.
- + Reversible.
- + High-precision metal drill chuck.
- + High concentricity.
- + Self-tightening drill chuck clamping jaws.
- + FEIN Sensitive Handle.
- + Variable speed control.
- + 5 metre cable.
- + 43 mm diameter collar for use in the drill jig.

Price includes

- + 1 SUPRA SKE single sheath metal quick clamping drill chuck
- + 1 additional handle

Product feature

- + Reversible rotation
- + Acceleration electronics

Application

Twist drilling

++

Tapping

++

Countersinking

++

+ suitable
++ well suitable

Technical data

TECHNICAL DATA

Input	500 W
Output	270 W
Speed, full load	0 - 460 / 0 - 1,350 rpm
Speed, no load	0 - 700 / 0 - 2,250 rpm
Torque at max. output power	20 / 7 Nm
Stall torque	50 / 16 Nm
Drill chuck clamping width	1.5 - 13 mm
Capacity in steel Ø	10 mm
capacity in Ø stainless steel	10 mm
Capacity in alu Ø	16 mm
Capacity in wood Ø	35 mm
Tapping	M 10
Thread of spindle	1/2"-20 UNF

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA Uncertainty of measured value KpA	84,8 dB 5 dB
Sound power level LWA Uncertainty of measured value KWA	92,8 dB 5 dB
Sound peak value LpCpeak Uncertainty of measured value KpCpeak	99,1 dB 5 dB
Vibration value 1 α_{hv} 3-way Uncertainty of measured value K α	$\alpha_{h,D}$ 3,0 m/s ² 1,5 m/s ²

Collar Ø	43 mm
Width across corners	23 mm
Cable with plug	5 m
Weight	2.00 kg

Application examples

