



BOZ 32-4 M

Four-Speed Hand Drill up to 32 mm

Universal four-speed drill with forward/reverse running, speed setting, MT3 tool mounting for heavy-duty drilling.

Product number: 7 202 51 60 00 0

Details

- + FEIN 1800 W high-power motor and mechanical 4-speed gearbox for high torque in heavy-duty drilling work.
- + Tool with forward/reverse running and electronic speed reduction for all drilling work, such as twist drilling, tap drilling, countersinking and reaming.
- + Extremely durable design for tough use thanks to highest quality materials and workmanship.
- + MT3 tool mounting.
- + Electronic torque shut-off.
- + Speed-controlled tacho electronics.
- + Able to handle extreme loads.
- + Metal gear head.
- + Cross handle.
- + For optimum use on FEIN magnetic drill jigs.
- + Wide range of accessories.
- + ** Torque slipping clutch.

Price includes

- + 1 additional handle
- + 1 drift key

Product feature

- + Reversible rotation
- + Torque slipping clutch
- + Speed preselection

Application

Sawing holes in sheet metal

+

Twist drilling

++

Tapping

++

Countersinking

++

Reaming

++

+ suitable
++ well suitable

Technical data

TECHNICAL DATA

Input	1,800 W
Output	1,100 W
Speed, full load	rpm
Load speed in speed 1	60 - 140 rpm
Load speed in speed 2	95 - 220 rpm
Load speed in speed 3	135 - 310 rpm
Load speed in speed 4	210 - 480 rpm
Speed, no load	rpm
Torque at max. output power	75 / 48 / 34 / 22 Nm
Idling speed in speed 1	60 - 140 rpm
Idling speed in speed 2	95 - 220 rpm
Idling speed in speed 3	135 - 310 rpm
Idling speed in speed 4	210 - 480 rpm
Stall torque	75 / 48 / 34 / 22 ** Nm
Tool Holder	MK 3
Capacity in steel Ø	32 mm
capacity in Ø stainless	20 mm

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA Uncertainty of measured value KpA	79,1 dB 3 dB
Sound power level LWA Uncertainty of measured value KWA	90,1 dB 3 dB
Sound peak value LpCpeak Uncertainty of measured value KpCpeak	93,4 dB 3 dB
Vibration value 1 α_{hv} 3-way Uncertainty of measured value K α	1,1 m/s ² 1,5 m/s ²

steel	
Capacity in alu Ø	60 mm
Capacity in wood Ø	70 mm
Tapping	M 24
Countersinking max. Ø	50 mm
Reaming max. Ø	30 mm
Collar Ø	65 mm
Width across corners	38 mm
Cable with plug	3.1 m
Weight according to EPTA	7.50 kg

Application examples





FEIN

