



BOP 10-2 set

Two-Speed Hand Drill up to 10 mm

Universal two-speed drill, up to 10 mm with ideal speed range for steel and stainless steel.

Product number: 7 205 54 61 00 0

Details

- Mechanical two-speed gearbox for optimum speed adjustment for a wide range of uses.
- FEIN high-power motor with good speed stability for constant drilling progress in almost any application.
- Metal gear head and distortion-free barrel-type motor housing for superb service life.

- + High-precision metal drill chuck.
- + High concentricity.
- + Self-tightening drill chuck clamping jaws.
- + FEIN Sensitive Handle.
- + Variable speed control.
- + 5 metre cable.
- + 43 mm diameter collar for use in the drill jig.

Price includes

+ Reversible.

- 1 SUPRA SKE single sheath metal quick clamping drill chuck
- + 1 plastic carrying case

Product feature

+ Reversible rotation

+ Acceleration electronics

+ 1 additional handle

Application



+ suitable

+ + well suitable

Twist drilling

Tapping

Countersinking

Technical data

TECHNICAL DATA

VIBRATION AND SOUND EMISSION VALUES

Input	500 W	Sound pressure level LpA Uncertainty of measured value	82 dB 3 dB
Output	270 W	КрА	
Speed, full load	0 - 460 / 0 - 1,350 rpm	Sound power level LWA Uncertainty of measured value KWA	93 dB 3 dB
Speed, no load	0 - 700 / 0 - 2,250 rpm	Sound peak value	96 dB
Torque at max. output power	20 / 7 Nm	LpCpeak Uncertainty of measured value KpCpeak	3 dB
Stall torque	50 / 16 Nm	Vibration value 1 $lpha$ hv 3-	α h,D 3,0 m/s²
Drill chuck clamping width	1.5 - 13 mm	Way Uncertainty of measured value Kα	1,5 m/s²
Capacity in steel Ø	10 mm		
capacity in Ø stainless steel	10 mm		
Capacity in alu Ø	16 mm		
Capacity in wood Ø	35 mm		
Tapping	M 10		
Thread of spindle	1/2"-20 UNF		



Collar Ø

Width across corners

Width across corners

Cable with plug

Weight according to EPTA

43 mm
23 mm
23 mm
5 m
2.00 kg