



CCG 18-115-10 PD-SEC Set 8Ah ProCORE AS

PROTAGO cordless angle grinder, 115 mm in diameter

Powerful cordless angle grinder with unique operating concept for particularly safe working.

Product number: 7 122 06 62 00 0

Details

- Maximum user protection thanks to the combination of a number of safety features.
- + Fewer accidents of the type frequently caused by improper use or negligence.
- Optimum performance, safe handling, perfect ergonomics and simple operation in all work situations.
- Extensive user protection provided by twohanded operation with AutoStop (dead man's switch) and permanently fitted additional handle, non-removable safety hood as well as kick-back monitoring, soft start, restart protection, electronic overload protection and braking function.
- Safe guidance in all work situations thanks to the additional handle, which can be adjusted into 6 positions.
- Short setup times thanks to the options of toolfree installation and setting, such as those for setting the safety hood, installing the protective cover for cutting work or changing consumables using quick-clamping nuts.
- Fatigue-free working thanks to narrow grip dimensions, compact design and a wellbalanced low weight.
- The tried and tested, highly reliable brushless FEIN PowerDrive motors guarantee a very long service life.

- Totally closed motor housing protects the motor from aggressive ceramic and mineral dusts.
 Separate motor electronics with dust guard in handle area.
- Powerful. 30% more efficiency than comparable universal motors with a rated output of 1080 W.
- Maintenance-free motor with innovative cooling ribs for optimum heat dissipation, including monitoring of temperature.
- Very smooth running and low-vibration working thanks to motor being decoupled from the housing and mounted separately and four additional vibration dampers.
- Ideal for every application. Optimum speeds, matched to a large number of abrasive materials and other materials using the infinitely variable, electronic speed preselection.
- Delivers the same power as an equivalent corded 1080 W angle grinder.
- Ideally equipped for every form of use. Mobile working with the L-BOXX system.
- Compatible with all 18 V AMPShare ProCORE batteries and chargers for even more power and flexibility. Also suitable for 18 V Bosch Professional cordless devices.
- COOLPACK 2.0 technology delivers a 135% longer battery life and therefore makes longer operating times possible.



 State-of-the-art cell technology and intelligent battery management deliver 87% more power than with conventional batteries.

 ProCORE Li-Ion battery with high-power cells, charge status indicator and "Electronic Cell Protection" (ECP). ECP protects against overload, overheating and total discharge.

Price includes

- + 1 Tool-free quick-clamping nut
- + 1 x protective cover for cutting work
- + 1 key
- + 2 ProCORE 18 V 8.0 Ah battery pack
- + 1 plastic tool case (L-BOXX 238)
- + 1 x GAL18 V-160 AS rapid charger

Product feature

- + Brake
- + Blockage monitoring
- + Electronic speed preselection

Application

- + Soft start
- + Electronic overload protection
- + AutoStop dead man's switch



Roughing-down

Deburring

Dividing

Brushing

Satin-finishing



Technical data

TECHNICAL DATA

++ well suitable

+ suitable

VIBRATION AND SOUND EMISSION VALUES

18 V	Sound pressure level LpA Uncertainty of measured value	80 dB 3 dB
Li-ion / ProCORE Li-ion	КрА	
18 V AMPShare	Sound power level LWA Uncertainty of measured value KWA	91 dB 3 dB
brushless	Sound peak value	94 dB
2,500 - 8,500 rpm	LpCpeak Uncertainty of measured value	3 dB
115 mm	Крореак	
115 mm	Vibration value 1 αhv 3- way Vibration value 2 αhv 3-way	7,7 m/s² 1,8 m/s²
M 14	Uncertainty of measured	1,5 m/s²
3.30 kg	value K α	
	Li-ion / ProCORE Li-ion 18 V AMPShare brushless 2,500 - 8,500 rpm 115 mm 115 mm M 14	Li-ion / ProCORE Li-ionUncertainty of measured value KpA18 V AMPShareSound power level LWA Uncertainty of measured value KWAbrushlessSound peak value LpCpeak Uncertainty of measured value KpCpeak2,500 - 8,500 rpmVibration value 1 αhv 3- Way Vibration value 2 αhv 3-wayM 14Uncertainty of measured value Kα

Application examples

2.30 kg

Weight without storage

battery





Kompatibel mit AMPShare-/ Bosch Professional 18 V Akkus. | Compatible with AMPShare/Bosch

Professional 18 V batteries. | Compatible avec les batteries 18 V AMPShare/Bosch Professional. | Compatible con baterías AMPShare/Bosch Professional de 18 V. | Compatibile con le batterie AMPShare / Bosch Professional da 18 V.























