

CG 17-150

Compact angle grinders, Ø 150 mm

Ergonomic 1700 W compact angle grinder with high power reserve for effective sanding and cutting.

Product number: 7 222 83 60 00 0



Details

- + Robust motor for daily use.
- + Long-life thanks to overload protection and long carbon brush service life.
- + Rapid work progress thanks to powerful motor.
- + Extensive user protection provided by kick-back monitoring, restart protection, soft start and anti-vibration handle.
- + Gearbox head can be rotated 90° for high versatility.
- + Abrasive materials can be changed at speed and without the need for any tools: quick-clamping nut included in scope of supply as standard.
- + Good ability to cope with overload thanks to direct motor cooling.
- + Industrial cable H07, length 4m.

Price includes

- + 1 wheel guard
- + 1 anti-vibration handle
- + 1 Tool-free quick-clamping nut
- + 1 key

Product feature

- + Soft start
- + Blockage monitoring
- + Kick-back check
- + Restart protection
- + Electronic overload protection

Application

Roughing-down



Deburring



Dividing

++

Brushing

++

+ suitable
++ well suitable

Technical data


TECHNICAL DATA

Input	1,700 W
Output	1,010 W
Speed, no load	9,300 rpm
Grinding disc Ø	150 mm
Elast. Backing pad Ø	150 mm
Flange	M 14
Cable with plug	4 m
Weight according to EPTA	2.50 kg
Weight according to EPTA	2.50 kg

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA Uncertainty of measured value KpA	92 dB 3 dB
Sound power level LWA Uncertainty of measured value KWA	103 dB 3 dB
Vibration value 1 α_{hv} 3-way	7 m/s ²
Vibration value 2 α_{hv} 3-way	2,5 m/s ²
Uncertainty of measured value K α	1,5 m/s ²

Application examples





FEIN

