



KBU 35 MQ

Universal magnetic core drill for up to 35 mm

Small and powerful single-speed universal magnetic core drill with clockwise/anti-clockwise operation, MT2 tool mounting and maximum functionality for flexible working on the construction site.

Product number: 7 270 55 61 00 0

Details

- + Extremely low-wear tool design with swivel-mounted motor cable protection hose for tough use in industry and manual trades.
- + Perfect power-to-weight ratio thanks to compact, weight-optimised design and FEIN 1 100 W high-power motor with tacho electronics for high speed stability for reliable and economical working.
- + With clockwise/anti-clockwise operation, electronic speed setting and a 260 mm stroke range, this is a universal tool for core drilling, twist drilling, tapping, countersinking and reaming.
- + Small with MT2 tool mounting.
- + Simple operating concept avoids mix-ups and can be clearly seen by the user.
- + Convenient magnetic holding force display helps the user to reliably position the tool.
- + High magnetic holding force.
- + Tilt sensor.
- + Additional magnetic switch in the drill jig.
- + Integrated coolant tank delivers long core drill bit lives.
- + Feed handwheel can be moved from one side to the other.
- + Speed saving "memory function".
- + Personal safety switch.
- + * Also available with accessories.

Price includes

- + 1 coolant tank
- + 1 swarf hook
- + 1 contact guard
- + 1 case
- + 1 lashing strap
- + 1 centering pin
- + 1 drift key

Product feature

- + Magnetic holding force display
- + Variable speed control
- + Speed-controlled electronics (tacho)
- + Reversible rotation
- + Memory function
- + Tilt sensor

Application

Core drilling in metal with a Ø up to 35 mm



Twist drills with drill chuck (DIN 338)



Twist drills with MK fitting (DIN 345)



Tapping





Countersinking

++

Reaming

++

Working overhead

++

Installation work

++

Workshop jobs

++

+ suitable

++ well suitable

Technical data

TECHNICAL DATA

Input	1,100 W
Output	550 W
Speed, full load	130 - 520 rpm
Tool Holder	MT 2
Carbide core drill bit max. Ø	35 mm
HSS core drill max. Ø	35 mm
Core drill, drilling depth max.	50(75)* mm
Twist drill max. Ø	18 mm
Tapping	M 14
Countersinking max. Ø	31 mm
Reaming max. Ø	18 mm
Core drill holder	QuickIN

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA Uncertainty of measured value KpA	82,3 dB 5 dB
Sound power level LWA Uncertainty of measured value KWA	93,3 dB 5 dB
Sound peak value LpCpeak Uncertainty of measured value KpCpeak	95,9 dB 5 dB
Vibration value 1 α_{hv} 3-way Uncertainty of measured value K α	$\alpha_{h,D} < 2,5 \text{ m/s}^2$ 1,5 m/s ²

Changing the core bit	tool-free
Stroke	135 mm
Total stroke range	260 mm
Magnetic holding power	10,000 N
Cable with plug	4 m
Weight according to EPTA	10.70 kg
Weight according to EPTA	10.70 kg

Application examples

