



ASAS 18-21 K AS Set 2 x 4 Ah

Compact cordless sabre saw

Compact, low-vibration sabre saw for mobile and universal use for cutting various materials, particularly well suited to hard-to-reach places. Including battery starter set of 2 x 4 Ah ProCORE batteries and rapid charger.

Product number: 7 133 01 62 00 0

Details

- + Rapid work progress when sawing thanks to the powerful DC motor.
- + The right solution for virtually all materials and applications: the SDS system for rapid, tool-free saw blade changes.
- + Optimised size and reduced vibrations for lowfatigue working.
- + LED light illuminates the working area.
- + Speed can be variably controlled via throttle.
- + Ergonomic design including soft grip.
- Compatible with all 18 V AMPShare ProCORE batteries and chargers for even more power and

- flexibility. Also suitable for 18 V Bosch Professional cordless devices.
- → Maximum work progress with AMPShare 18V ProCORE batteries: COOLPACK 2.0 technology delivers a 135% longer battery life. State-of-theart cell technology and intelligent battery management deliver 87% more power than with conventional batteries. "Electronic Cell Protection" (ECP) protects the battery from overload, overheating and total discharge.
- + Ideally equipped for every form of use. Mobile working with the L-BOXX system.

Price includes

- + 1 x BIM 130 T18 MS sabre saw blade
- + 1 rapid charger GAL 1880 CV AS
- + 1 tool case (L-Boxx 136)

- + 1 x BIM 130 T5/8 WP sabre saw blade
- + 2 x ProCORE 18 V 4.0 Ah AS battery pack

Technical data

TECHNICAL DATA

VIBRATION AND SOUND EMISSION VALUES



Battery voltage

18 V

Li-ion / ProCORE Li-ion

Battery interface

Battery compatibility

18 V AMPShare

Strokes

0 - 3 050 rpm

wood

200 mm

Metal profiles and metal pipes

100 mm

Stroke of blade

21 mm

Width

78 mm

Height

177 mm

Length

367 mm

2.00 kg

Weight without storage battery

Sound pressure level LpA Uncertainty of measured value KpA

Sound power level LWA Uncertainty of measured value KWA

Uncertainty of measured value KpCpeak Vibration value 1 α hv 3-way

Uncertainty of measured value K α

82 dB 5 dB

93 dB 5 dB

5 dB

8 m/s²

1,5 m/s²

Application examples









