



## STS 325 R

Hacksaws for pipes up to Ø 440 mm

Compressed air hacksaw for pipes and profiled sections.

Product number: 7 534 08 00 00 0

### Details

- + Ideally suited for trimming pipes and shaped section made of steel, cast-iron, autoclaved aerated concrete and plastics.
- + Clamp and feed device available for profiles and pipes from Ø 80 mm to Ø 400 mm.
- + Adjustable clamping devices permit mitre cuts up to 45° as well.
- + Clamp and feed device.
- + Adjustable clamping fixtures.
- + \* With chain extension.

### Price includes

- + 2 saw blades
- + 1 set of keys
- + 1 additional handle
- + 1 hose coupling

### Product feature

- + aus\_druckluftantrieb

### Technical data

#### TECHNICAL DATA

|                    |                         |
|--------------------|-------------------------|
| Operating pressure | 6 bar                   |
| Air consumption    | 1.5 m <sup>3</sup> /min |
| Output             | 1,100 W                 |
| Strokes            | 330 rpm                 |
| Stroke of blade    | 60 mm                   |
| Pipes up to Ø      | 440 * mm                |

#### VIBRATION AND SOUND EMISSION VALUES

|                                                                         |                           |
|-------------------------------------------------------------------------|---------------------------|
| Sound pressure level LpA<br>Uncertainty of measured value<br>KpA        | 81 dB<br>3 dB             |
| Sound power level LWA<br>Uncertainty of measured value<br>KWA           | 92 dB<br>3 dB             |
| Sound peak value<br>LpCpeak<br>Uncertainty of measured value<br>KpCpeak | 102 dB<br>3 dB            |
|                                                                         | αh,D 7,1 m/s <sup>2</sup> |



# FEIN

profiles up to W x H

290x500 mm

Weight according to EPTA

7.20 kg

Vibration value 1  $\alpha_{hv}$  3-  
way  
Uncertainty of measured value  
 $K\alpha$

1,5 m/s<sup>2</sup>

## Application examples

