

		Share	
Powered by	\oplus	возсн	
			Tem
		0	and a fill
		F	
		5	
		E.K	BFEIN

ABLK 18 1.6 E AS Set 1x 5 Ah

Cordless nibbler up to 1.6 mm

Compact and curve-compatible nibbler for roof and façade construction. Precise cuts in trapezoid and corrugated sheet metals and profiles. Includes battery charger GAL 1880 CV AS, 1x Li-ion storage batteries GBA 18V 5.0 Ah AS, additional punch and die set, permanent marker, painter's tape and metre rule.

Product number: 7 132 11 63 00 0



Details

- 66 m cutting capacity (in 0.8 mm sheet metal) with one battery charge (5 Ah).
- Cutting direction setting can be changed in 45° steps up to 360° using tool-free pivoting cutting head.
- Optimum handling due to extremely slim gearbox head.
- 1.5 m/min cutting speed for excellent work progress.
- + Variable cutting speed due to electronically adjustable speed control.
- + Brief overlapping area up to 2.6 mm.
- Rotating punch for a service life which is now up to 30 % longer.
- Proven MultiMaster motor with outstanding performance and stability.

- Compatible with AMPShare/Bosch Professional 18 V batteries.
- Maximum work progress with AMPShare 18V storage batteries: COOLPACK 1.0 technology ensures a longer storage battery life compared with batteries without COOLPACK technology and therefore makes longer operating periods possible. ECP protects the storage battery against overload, overheating and total discharge.
- + Low operating costs. Punch and die are replaced independently of one another.
- + QuickIN quick change system for die and punch.
- Ideally equipped for every job. Mobile working with the L-BOXX system.
- State-of-the-art cell technology and intelligent battery management deliver 87% more power than with conventional batteries.

Price includes

- + 1 die (30109141003) fitted
- + 1 cutting head (30109154007) mounted
- + 1 punch and die set (30109169030)
- + 1 painter's tape (32133038000)
- 1 Li-Ion storage battery GBA 18 V
 5.0 Ah AS (92604346020)
- + 1 tool case (L-Boxx 136)

Product feature

- + Rotating round punch
- + QuickIN

Application

Curve cuts

- + 1 punch (6 36 02 050 00 0)
- + 1 socket head wrench 6 mm
- + 1 permanent marker (32133037000)
- + 1 metre rule (18750283000)
- + 1 rapid charger GAL 1880 CV AS (92604335010)
- + Cutting direction
- + Adjustable stroke



Coil sections

Interior cut-outs


Profile sections

Notches

Technical data

Battery voltage

TECHNICAL DATA



VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA 87,8 dB Uncertainty of measured value 3 dB КрА Sound power level LWA 98,8 dB Uncertainty of measured value 3 dB KWA 109,6 dB Sound peak value LpCpeak Uncertainty of measured value 3 dB KpCpeak Vibration value 1 α hv 3ah 12,1 m/s² way ղ² Uncertainty of measured value 1,5 m/s² Κα ղ²

+ + well suitable

Battery capacity
Battery compatibility
Battery interface
Strokes
Cutting speed
Steel up to 400 N/mm ²
Steel up to 600 N/mm ²
Steel up to 800 N/mm ²
Non-ferrous metals up to 250 N/mm ²
Cutting width
Immersion Ø with die

Rad. of smallest curve (inside/outside)

18 V
5 Ah
Li-ion / ProCORE Li-ion
18 V AMPShare
850 - 1 350 rpm
1.5 m/min
1.6 mm
1 mm
0.7 mm
2.5 mm
5 mm
22 mm
30 / 35 mm



Weight without storage battery

1.71 kg

Application examples

