



FEIN



FEIN Dustex 35 MX AC

Wet / dry dust extractor

Powerful, professional wet/dry dust extractor of dust class M with fully automatic filter cleaning for attachment of various case systems including extensive accessories.

Product number: 9 20 32 060 00 0

Details

- + Approved for holding hazardous dusts of class M.
- + Tool cases of various systems can be simply positioned on the extraction head and secured.
- + Fully automatic filter cleaning (AC) makes the flat fold filter last longer for uninterrupted working.
- + Ergonomic transport of the complete unit, including power tool and extractor, thanks to push bar and case and accessory attachment.
- + Reliable suction of different types of dirt from liquids to fine dusts.
- + With PES flat fold filter and electronic shut-off for outstanding wet extraction performance.
- + Auto start socket with switch-on delay to avoid power surges.
- + Infinitely variable suction force regulation on the extractor.
- + The 7.5 m mains cable and 4 m hose provide a large working radius.
- + Anti-static function for preventing static charging during work - electrostatically discharging.

Price includes

- + 1 push bar
- + 1 PES flat fold filter
- + 1 disposal bag
- + 1x 4 m ES suction hose, diameter 35 mm
- + 1 tool collar with suction force regulation
- + 1 stepped collar
- + 2 suction pipes (metal), 1 combi nozzle with interchangeable inserts, 1 crevice nozzle, 1 suction brush, 1 elbow

Product feature

- + Automatic start/stop
- + Soft start
- + Automatic filter cleaning
- + Antistatic preparation
- + Anti-static function
- + Case storage
- + Dust class

Technical data

TECHNICAL DATA

Maximum power input

1,380 W

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA
Uncertainty of measured value
KpA

67 dB
2 dB



FEIN

Air flow	4,320 l/min	Sound power level LWA	81 dB
Max. vacuum	254 hPa	Uncertainty of measured value KWA	2 dB
Tank volume	35 l	Vibration value 1 α_{hv} 3-way	< 2,5 m/s ²
Cable with plug	7.5 m		
Sound pressure level	67 dB		
Weight according to EPTA	14.10 kg		

Application examples

