



FEIN



AKFH 18-5T CORE 18 V Beveler AS

Cordless beveler up to 5" with accessory set

Powerful cordless beveler combined with the perfect accessories for creating a 45° bevel. For the preparation of subsequent coatings for flexible work in the workshop and on construction sites. Includes one CORE 18 V 8 Ah AS battery and one GAL 18V-160 AS charger.

Product number: 7 138 05 62 09 0

Details

- + Unpack the tool and get started: The set is designed for making bevels on flat materials, sheet metal and containers, inner and outer edges, and contours.
- + High removal rate, low effort, and infinitely variable speed adjustment for different materials.
- + Ergonomic due to its light weight and compact design.
- + Extensive user protection due to soft start, restart protection, jam monitoring, and electronic overload protection.
- + FEIN brushless PowerDrive motor for high performance and durability.
- + Extensive user protection due to soft start, restart protection, jam monitoring, and electronic overload protection.
- + Compatible with all CORE 18 V AMPShare batteries and chargers, for even more power and flexibility. Also suitable for 18 V Bosch Professional cordless tools.
- + COOLPACK 2.0 technology ensures a 135% longer battery service life, enabling longer operation time.
- + State-of-the-art cell technology and intelligent battery management deliver 87% more power than conventional batteries.
- + CORE 18 V Li-ion battery with Highpower cells, charge indicator and electronic cell protection (ECP). ECP protects batteries against overloading, overheating and deep discharge.
- + Perfectly equipped for any application. Mobile work with the L-BOXX system.

Price includes

- + 1 AKFH 18-5 AS including 45° milling head
- + 1 Allen key 4 mm
- + 1 cutting paste
- + 1 Ø 21.69 mm guide roller for 45° bevel and 2.5 mm radius
- + 1 GAL18 V-160 AS rapid charger
- + 3 retaining screws SX
- + 1 Torx TX 15 screwdriver
- + 1 package of 10 SX bevel inserts for universal application
- + 1 CORE 18 V 8.0 Ah battery pack
- + 1 plastic carrying case (L-BOXX 238)

Product feature

- + Soft-start
- + Jam monitoring
- + Speed preselection
- + Self-start lock
- + Electronic overload protection

Application

Installation work



Chamfer length up to 1/4 [5] in[mm] at 45°



+ suitable
++ well suitable

Technical data

TECHNICAL DATA

Battery voltage	18 V
Battery compatibility	Li-ion / CORE 18 V Li-ions
Battery interface	18 V AMPShare
No load speed	2,400 - 7,500
Max. chamfer length at 45°	3/16 [5] in[mm]
Max. chamfer height at 45°	1/8 [3.5] in[mm]
Chamfer angle	45°
Cutting head mounting	3x SX insert
Support plate Ø	3-7/8 [98] in[mm]
Weight without battery	5.56 [2.52] lbs[kg]

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA Measurement uncertainty of the measured value KpA	85 dB 3 dB
Sound power level LWA Measurement uncertainty of the measured value KWA	96 dB 3 dB
Peak sound value LpCpeak Measurement uncertainty of the measured value KpCpeak	100 dB 3 dB
Vibration value 1 α_{hv} 3-way Vibration value 2 α_{hv} 3-way	3,1 m/s ² 4,5 m/s ²
Measurement uncertainty of the measured value K α	1,5 m/s ²

Application examples

