



## ABS 18 Q Select

### 2-speed cordless drill/driver

With brushless motor and QuickIN interface. Ideal for drilling up to 13 mm and tapping up to M10.

Product number: 7 113 22 64 00 0

### Details

- + Brushless FEIN PowerDrive motor with 30% greater efficiency and longer service life.
- + QuickIN accessory interface for all QuickIN accessories. Fast change between applications.
- + MultiVolt-interface. Cordless tool can be used with all FEIN li-ion batteries (12-18 V).
- + 2-speed solid metal gearbox for drilling in metal and self-drilling screws.
- + QuickIN solid metal drill chuck with carbide jaws and 1,062 in/lb clamping force.
- + Mechanical torque setting.
- + Compact design.
- + 900 screw applications (3/16 x 1-9/16 [5 x 40] in[mm] in wood) with one battery charge (3 Ah).
- + One charger for all voltage classes of FEIN Li-ion batteries.
- + The battery capacity can be read directly on the battery.
- + FEIN SafetyCell technology. Protects the battery and the machine from overloading, overheating and deep discharge.
- + User safe with restart and electronic overload protection.

### Price includes

- + 1 QuickIN drill chuck 1,062 [120] in/lbs[Nm]
- + 1 magnetic bit holder
- + 1 belt clip
- + 1 tool case

### Product feature

- + Removable drill chuck

### Technical data

#### TECHNICAL DATA

## VIBRATION AND SOUND EMISSION VALUES

Battery voltage	18 V	Sound pressure level LpA Measurement uncertainty of the measured value KpA	76 dB 3 dB
Battery compatibility	Li-ion / HighPower Li-ions	Sound power level LWA Measurement uncertainty of the measured value KWA	87 dB 3 dB
Battery interface	MultiVolt	Peak sound value LpCpeak Measurement uncertainty of the measured value KpCpeak	89 dB 3 dB
Motor	brushless	Vibration value 1 $\alpha_{hv}$ 3-way	$\alpha_{h,D}$ 1,5 m/s <sup>2</sup>
Gearbox	2-speed	Vibration value 2 $\alpha_{hv}$ 3-way	$\alpha_h$ 0,6 m/s <sup>2</sup>
Accessory interface	QuickIN	Measurement uncertainty of the measured value K $\alpha$	1,5 m/s <sup>2</sup>
No load speed	450 / 2,000		
Max. torque (hard/soft)	531 [60] / 283 [32] in/lbs[Nm]		
Torque steps	22 + 1		
Chuck capacity	1/16 [1.5] - 1/2 [13] in[mm]		
Fastening	3/8 [8] x 11-3/4 [300] in[mm]		
Twist drill diameter capacity in steel	1/2 [13] in[mm]		
Holesaw diameter capacity in wood	1-31/32 [50] in[mm]		
Tapping	M 10		
Weight without battery	2.87 [1.30] lbs[kg]		

## Application examples

