



ROTO-STAR III

Rotary Welding Positioner

Rotary welding positioner with chuck for work pieces up to 250 [113] lbs[kg] and 4-1/2 [114] in[mm] diameter with standard foot pedal and control box.

Product number: 3 13 43 790 14 0

Details

- + Provides stable work platform for increased productivity and seamless welds.
- + Rotates a full 360 degree at a steady speed to weld safely and quickly.
- + Pitch up to a 90 degree angle at 15 degrees increments offering enhanced mobility and functionality.
- + Increases safety by eliminating operator fatigue.

- + Increases production by reducing handling and by maneuvering of parts.
- + Light weight and heavy duty construction.
- + Provides stable work area to perfect high quality welds.
- + Optional rotary 16 [406] in[mm] surface plate.
- + Optional variable speed foot pedal and with control box.

Price includes

+ 1 chuck

+ 1 control box

+ 1 standard foot pedal

Technical data

TECHNICAL DATA

Current/Voltage

Chuck

Rotation at 0°

Vertical carrying capacity

1 x 120 V

8 [203] in[mm]

20 [508] in[mm]

250 [113.5] lbs[kg]



Horizontal carrying capacity	150 [68] lbs[kg]
Internal chuck dia.	2-1/2 [64] in[mm]
Spindle speed	0-8 rpm
Tilt adjustment	0-90°
Grounding output	300 Amp
Weight	90 [41] lbs[kg]