



JMU 137 MQW

Universal magnetic core drill up to 1-3/8 in [35 mm]

Small, long-stroke, single-speed universal magnetic core drill with forward / reverse rotation, MT2 tool mount and maximum functionality for flexible work on the construction site.

Product number: 7 270 56 61 12 0

Details

- + Extremely wear-resistant tool concept with swivel-mounted motor cable protection hose for tough conditions in industry and skilled trades.
- + Perfect power-to-weight ratio, thanks to compact, weight-optimized design and FEIN 1 100 W high-performance motor with tacho electronics for high speed stability for reliable and efficient operation.
- + Right/left rotation, electronic speed adjustment and 10-1/4 [260] in[mm] stroke range enable universal work applications such as core drilling, spiral drilling, tapping as well as countersinking and reaming.
- + Small, with MT2 tool mount.
- + Simple and error-proof control concept in the operator's field of view.
- + A Convenient magnetic holding force indicator supports the safe positioning of the tool.
- + High magnetic holding force.
- + Motion sensor.
- + Additional magnet switch in the drill stand.
- + Integrated coolant tank ensures high core drill tool life.
- + Hand feed wheel can be mounted on either side.
- + "Memory function" speed storage.
- + * optional using accessory.

Price includes

- + 1 coolant tank
- + 1 chip hook
- + 1 chip guard
- + 1 safety strap
- + 1 pilot pin
- + 1 case

Product feature

- + Magnet holding force display
- + Electronic speed setting
- + Speed-controlled tacho electronics
- + Forward/reverse operation
- + Memory function
- + Tilt sensor



FEIN

Application



Mag base drilling metal up to 1-1/2" dia.

++

Twist drilling with drill chuck

+

Twist drilling with MT fitting

++

Tapping

++

Countersinking

++

Reaming

++

Performing overhead work

++

Installation work

++

Workshop jobs

++

+ suitable

++ well suitable

Technical data

TECHNICAL DATA

Power consumption

1,100 W

Power output

550 W

Full load speed

130 - 520

Tool mount

MT 2

Carbide cutter max. dia.

1-3/8 [35] in[mm]

HSS cutter max. dia.

1-3/8 [35] in[mm]

Cutter max. drilling depth

2 [50] (3 [75])* in[mm]

Twist drill max. dia.

3/4 [18] in[mm]

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA
Measurement uncertainty of
the measured value KpA

82,3 dB
5 dB

Sound power level LWA
Measurement uncertainty of
the measured value KWA

93,3 dB
5 dB

Peak sound value
LpCpeak
Measurement uncertainty of
the measured value KpCpeak

95,9 dB
5 dB

Vibration value 1 α_{hv} 3-
way
Measurement uncertainty of
the measured value K α

$\alpha_{h,D} < 2,5 \text{ m/s}^2$
1,5 m/s^2

Tapping	1/2"
Max. countersinking dia.	1-1/4 [31] in[mm]
Reaming max. dia.	3/4 [18] in[mm]
Cutter holder	3/4" straight shank
Cutter change	tool-free
Stroke	5-5/16 [135] in[mm]
Total stroke range	10-1/4 [260] in[mm]
Magnetic holding force	2248 [10,000] lbs[N]
Cable with plug	13.1 [4] ft[m]
Weight	23.59 [10.70] lbs[kg]
Weight	23.59 lbs

Application examples

