



JCM 200 QX

Mag Drill unit up to 2 [50] in[mm]

Lightweight with 2-speed gearbox and easy operation for efficient drilling in the workshop and on the construction site.

Product number: 7 270 45 61 12 0

Details

- + Compact with high functionality for universal use on the construction site and in the workshop.
- + Simple and error-proof control concept in the operator's field of view.
- + Double drill motor guides enable use of the longest annular cutters.
- + Reversible
- + Electronic speed control.
- + High-power motor with stable speed.
- + High magnetic holding force.
- + A Convenient magnetic holding force indicator supports the safe positioning of the tool.
- + Integrated coolant tank ensures high core drill tool life.
- + Hand feed wheel can be mounted on either side.

Price includes

- + 1 coolant tank
- + 1 chip hook
- + 1 chip guard
- + 1 safety strap
- + 1 pilot pin 4 1/8 in (105 mm)
- + 1 case

Product feature

- + Magnet monitor system
- + Forward/reverse operation
- + Memory function
- + Magnet holding force display
- + Electronic speed setting
- + Speed-controlled tacho electronics

Application

Mag base drilling metal up to 1-1/2" dia.





FEIN

Mag base drilling metal up to 2 in dia.

++

Twist drilling with drill chuck

+

Tapping

++

Countersinking

++

Reaming

++

Performing overhead work

+

Installation work

++

Workshop jobs

++

+ suitable

++ well suitable

Technical data

TECHNICAL DATA

Power consumption

1,200 W

Power output

640 W

Load speed: 1st gear

130 - 260 rpm

Load speed: 2nd gear

260 - 520 rpm

Carbide cutter max. dia.

2 [50] in[mm]

HSS cutter max. dia.

1-9/16 [40] in[mm]

Cutter max. drilling depth

2 [50] in[mm]

Twist drill max. dia.

5/8 [16] in[mm]

Tapping

M 16

Max. countersinking dia.

1-1/4 [31] in[mm]

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA
Measurement uncertainty of
the measured value KpA

82,1 dB
5 dB

Sound power level LWA
Measurement uncertainty of
the measured value KWA

93,1 dB
5 dB

Peak sound value
LpCpeak
Measurement uncertainty of
the measured value KpCpeak

96,2 dB
5 dB



Reaming max. dia.	5/8 [16] in[mm]
Cutter holder	3/4" straight shank
Cutter change	tool-free
Stroke	5-11/16 [145] in[mm]
Total stroke range	12-3/8 [315] in[mm]
Cable with plug	13.1 [4] ft[m]

Application examples

