



MULTIMASTER MM 500 Plus Top

Oscillating MultiTools - MM 500

Our high-performance MULTIMASTER 500 makes quick work of interior construction and renovation jobs. Includes over 30 accessories for sawing in wood, metal, plastics, removing tiles, cutting silicone caulking and carpeting, and removing residual tile adhesive.

Product number: 7 229 67 70 09 0

Details

- + Anti-vibration system: Permanently safe, pleasant working conditions with minimum vibrations and outstanding noise damping.
- + StarlockPlus tool mounting: Work faster and with higher precision thanks to 100% no-loss power transmission.
- + QuickIN: Tool change in under 3 seconds with a patented, tool-free, FEIN rapid-clamping system.
- + With the StarlockPlus tool mounting, you have access to around 100 FEIN accessories in the Starlock and StarlockPlus performance categories.
- + 350 W FEIN motor: Overload-proof, high-performance motor with high proportion of copper for higher cutting speed and rapid work progress.
- + Tacho generator: Constant speeds, even under load, and infinitely variable electronic speed control.
- + Metal drive head: High load capacity and maximum service life, since all drive head parts are made of metal.
- + Mechanical interface: For stationary use in the table or drill jig holders, or to attach depth stops.
- + Industrial cable: Large operating radius thanks to the 5 m, fine-stranded rubber-clad cable in industrial quality.
- + Perfectly equipped for any application. Mobile work with the L-BOXX system.

Price includes

- + 1 E-Cut Long Life saw blade (10 mm)
- + 2 E-Cut Long Life saw blades (2-9/16 [65] in[mm])
- + 1 HM saw blade (Ø 3 [75] in[mm])
- + 1 rigid scraper blade
- + 20 perforated sanding sheets (5 each of grits 60, 80, 120, 180)
- + 1 tool case (L-BOXX 136)
- + 2 E-Cut Long Life saw blades (1-3/8 [35] in[mm])
- + 1 E-Cut Carbide Pro saw blade (1-1/4 [32] in[mm])
- + 1 carbide rasp (triangular)
- + 1 perforated sanding pad
- + 1 dust extraction device

Technical data

TECHNICAL DATA

Power consumption

350 W

Oscillations

10,000 - 19,500 opm

Tool mount

StarlockPlus

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA
Measurement uncertainty of the measured value KpA

72 dB
3 dB

Sound power level LWA
Measurement uncertainty of the measured value KWA

83 dB
3 dB

| | | | |
|-----------------|---------------------|---|-------|
| Tool change | QuickIN | Peak sound value | 84 dB |
| Range | 2 x 1,7° | LpCpeak | 3 dB |
| Cable with plug | 16.4 [5] ft[m] | Measurement uncertainty of the measured value KpCpeak | |
| Weight | 3.09 [1.40] lbs[kg] | | |
| Weight | 3.09 lbs | | |

Application examples

