



Cordless MULTIMASTER AMM 500 AS 2 Ah with nylon bag

Cordless oscillating multi-tool

The high-performance cordless MultiTool for rapid work progress (both interior construction and renovation) with over 18 accessories – for sawing in wood and metal, sanding, removing tiles, and more.

Product number: 7 129 38 65 09 0

Details

- + Anti-vibration system: Permanently safe, pleasant working conditions with minimum vibrations and outstanding noise damping.
- + StarlockPlus tool mounting: Work faster and with higher precision thanks to 100% no-loss power transmission.
- + QuickIN: Tool change in under 3 seconds with a patented, tool-free, FEIN rapid-clamping system.
- + With the StarlockPlus tool mounting, you have access to around 100 FEIN accessories in the Starlock and StarlockPlus performance categories.
- + DC motor: Effective, high-torque motor technology for output that is virtually identical to that of the model with a cord.
- + Tacho generator: Constant speeds, even under load, and infinitely variable electronic speed control.
- + Metal drive head: High load capacity and maximum service life, since all drive head parts are made of metal.
- + Mechanical interface: For stationary use in the table or drill jig holders, or to attach depth stops.
- + Electronic cell protection (ECP): ECP protects storage batteries against overloading, overheating and deep discharge.
- + COOLPACK technology ensures a longer storage battery service life, enabling longer operation times.
- + The battery capacity can be read directly on the battery.
- + Compatible with AMPShare/Bosch Professional 18 V batteries from 2008 on.

Price includes

- + 1 saw blade SLP E-Cut LL BIM 50x50
- + 15 sanding sheets (5 each of grits 60, 120, 180)
- + 1 rapid charger GAL 1880 CV AS
- + 1 nylon tool bag
- + 1 saw blade SLP E-Cut LL BIM 50x35
- + 1 perforated sanding pad
- + 1 Li-ion battery pack (18 V / 2 Ah)

Technical data

TECHNICAL DATA

Battery voltage	18 V
Battery capacity	2 Ah
Battery compatibility	Li-ion / CORE 18 V Li-ions
Battery interface	18 V AMPShare
Oscillations	11,000 - 18,500 opm
Tool mount	StarlockPlus
Tool change	QuickIN
Range	2 x 1,7°
Weight without battery	2.87 [1.30] lbs[kg]

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA
Measurement uncertainty of the measured value KpA

76,0 dB
3 dB

Sound power level LWA
Measurement uncertainty of the measured value KWA

84,0 dB
3 dB

Peak sound value
LpCpeak

88,4 dB

Measurement uncertainty of the measured value KpCpeak

3 dB

Application examples



Powered by  BOSCH

Compatible with AMPShare/Bosch Professional 18 V batteries. |

Compatible avec les batteries 18 V AMPShare/Bosch Professional. |

Compatible con baterías AMPShare/Bosch Professional de 18 V.



