



MULTIMASTER MM 500 Plus

Oscillating MultiTools - MM 500

Our high-performance MULTIMASTER 500 makes quick work of interior construction and renovation jobs. Includes a bimetal saw blade for working in wood, metal and plastic.

Product number: 7 229 67 69 09 0

Details

- + Anti-vibration system: Permanently safe, pleasant working conditions with minimum vibrations and outstanding noise damping.
- + StarlockPlus tool mounting: Work faster and with higher precision thanks to 100% no-loss power transmission.
- + QuickIN: Tool change in under 3 seconds with a patented, tool-free, FEIN rapid-clamping system.
- + With the StarlockPlus tool mounting, you have access to around 100 FEIN accessories in the Starlock and StarlockPlus performance categories.
- + 350 W FEIN motor: Overload-proof, high-performance motor with high proportion of copper for higher cutting speed and rapid work progress.
- + Tacho generator: Constant speeds, even under load, and infinitely variable electronic speed control.
- + Metal drive head: High load capacity and maximum service life, since all drive head parts are made of metal.
- + Mechanical interface: For stationary use in the table or drill jig holders, or to attach depth stops.
- + Industrial cable: Large operating radius thanks to the 5 m, fine-stranded rubber-clad cable in industrial quality.
- + Easily transported with our stackable L-BOXX system.

Price includes

- + 1 universal E-Cut saw blade 1-3/4 in (44 mm) (type 152)
- + 1 tool case (L-BOXX 136)

Technical data

TECHNICAL DATA

Power consumption

350 W

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA

75,6 dB

Measurement uncertainty of the



FEIN

Oscillations	- opm	measured value KpA	3 dB
Tool mount	StarlockPlus	Sound power level LWA Measurement uncertainty of the measured value KWA	83,6 dB 3 dB
Tool change	QuickIN	Peak sound value LpCpeak Measurement uncertainty of the measured value KpCpeak	90,3 dB 3 dB
Range	2 x 1,7°		
Cable with plug	16.4 [5] ft[m]		
Weight	3.09 [1.40] lbs[kg]		

Application examples

