



## BLK 2.0 E

### Nibbler up to 14 gauge

Compact nibbler with unlimited curve compatibility for corners and edges.

Product number: 7 232 40 60 12 0

### Details

- + High curve precision due to special cutting head geometry. Nibbler can turn on the spot.
- + Especially well-suited for cutting edged sheet metal with a minimum bend radius of 1/8 in [3 mm].
- + Cutting direction setting can be changed in 45° increments up to 360° using tool-free rotating cutting head.
- + QuickIN rapid change system.
- + Optimal ergonomics.
- + Motor with outstanding performance and durability.
- + Ideal for cut-outs.
- + Optimally suited for template cuts.
- + Chip protection mesh on vent slots.
- + 16 ft. [5 m] cable.
- + Stainless steel up to 19 gauge [1.0 mm].

### Price includes

- + 1 die (3 13 09 040 0 02)
- + 1 punch (6 36 02 051 00 9)

### Product feature

- + Cutting direction
- + Variable speed
- + QuickIN

### Application

Curve cuts

++

Inside cutouts

++

Profile cuts

++

Notches

++

+ suitable

++ well suitable

## Technical data

### TECHNICAL DATA

Power consumption	350 W
Power output	210 W
Strokes	500 - 1,000 spm
Cutting speed	3.3 [1] ft/min[m/min]
Steel 58,000 lbf/in <sup>2</sup>	5/64 [2] in[mm]
Steel 87,000 lbf/in <sup>2</sup>	1/16 [1.5] in[mm]
Steel 116,000 lbf/in <sup>2</sup>	0/1 [1] in[mm]
Non-ferrous metals up to 36,000 lbf/in <sup>2</sup>	3/32 [2.5] in[mm]
Cutting width	5/16 [8] in[mm]
Immersion Ø with die	11/16 [18] in[mm]
Radius of smallest curve (inside/outside)	1/4 [4] / in[mm]
Cable with plug	16.4 [5] ft[m]
Weight	3.97 [1.80] lbs[kg]

### VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA Measurement uncertainty of the measured value KpA	80 dB 3 dB
Sound power level LWA Measurement uncertainty of the measured value KWA	91 dB 3 dB
Peak sound value LpCpeak Measurement uncertainty of the measured value KpCpeak	91 dB 3 dB
Vibration value 1 $\alpha_{hv}$ 3-way Measurement uncertainty of the measured value K $\alpha$	7,3 m/s <sup>2</sup> 1,5 m/s <sup>2</sup>

Weight

3.97 lbs

## Application examples

