



BLK 5.0

Nibbler up to 6 gauge

Powerful nibbler for heavy dismantling and cutting applications.

Product number: 7 232 31 12 63 4

Details

- + Powerful 1,200 watt motor for outstanding performance while maintaining excellent ergonomics.
- + Cuts over 90° edges, for example on guard rails or tanks.
- + Cutting direction can be adjusted in three 90° steps without the need for tools.
- + Optimum power-to-weight ratio.
- + Long tool life of punch and die.
- + Chip protection mesh on vent slots.
- + Handle can be rotated 180°.
- + 16 ft. [5 m] cable.
- + Stainless steel up to 13 gauge [2.5 mm].
- + Wide range of accessories.

Price includes

- + 1 wrench
- + 1 punch (3 13 09 110 00 4)
- + 1 additional handle
- + 1 die (3 13 09 107 00 0)
- + 1 cutting head

Product feature

- + Cutting direction

Application



Curve cuts



+ suitable

++ well suitable

Technical data

TECHNICAL DATA

Power consumption	1,200 W
Power output	750 W
Strokes	750 spm
Cutting speed	4 [1.3] ft/min[m/min]
Steel 58,000 lbf/in ²	13/64 [5] in[mm]
Steel 87,000 lbf/in ²	1/8 [3.3] in[mm]
Steel 116,000 lbf/in ²	3/32 [2.5] in[mm]
Non-ferrous metals up to 36,000 lbf/in ²	9/32 [7] in[mm]
Cutting width	5/16 [8] in[mm]
Immersion Ø with die	1-11/16 [43] in[mm]
Radius of smallest curve (inside/outside)	3-1/2 [86] / 3-3/4 [94] in[mm]
Cable with plug	16 [5] ft[m]
Weight	8.38 lbs

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA
Measurement uncertainty of the measured value KpA

85 dB
3 dB

Sound power level LWA
Measurement uncertainty of the measured value KWA

96 dB
3 dB

Peak sound value

LpCpeak
Measurement uncertainty of the measured value KpCpeak

100 dB

3 dB

Vibration value 1 α_{hv} 3-way
Measurement uncertainty of the measured value K α

10 m/s²

1,5 m/s²

Application examples



FEIN

