



ABLS 18 1.6 E AS Set

Cordless sheet metal shears for up to 16 gauge [1.6mm]

Handy, curve-compatible cordless sheet metal shears for cutting and trimming thin sheet metal. Includes BC 1880 CV AS charger, 2x CORE 18V 4.0 Ah AS lithium-ion batteries, second plunger and table blade, permanent marker and a painter's tape.

Product number: 7 130 06 65 09 0

Details

- + 725 [221] ft[m] cutting capacity (in 22 [0.8] gauge [mm] sheet metal) with one battery charge (4 Ah).
- + Outstanding ergonomics and compact design for optimal mobility of the shear.
- + Indexible cutting blades with four sides for clean and burr-free cutting with low operating costs.
- + Good curve precision with low sheet-metal distortion.
- + Perfect for trimming and cutting.
- + Unrestricted view of the cutting line.
- + Proven MultiMaster motor with outstanding power and durability.
- + Compatible with AMPShare/Bosch Professional 18 V batteries from 2008 on.
- + Maximum cutting speed with AMPShare 18V batteries: COOLPACK 2.0 technology ensures a longer battery service life in comparison to batteries without COOLPACK technology. It makes longer operation times possible. ECP protects batteries against overloading, overheating and deep discharge.
- + Perfectly equipped for any application. Mobile work with the L-BOXX system.
- + State-of-the-art cell technology and intelligent battery management deliver 87% more power than conventional batteries.

Price includes

- + 2 pair of blades (31308072000), mounted
- + 1 Allen key 3 mm
- + 1 permanent marker (32133037000)
- + 2 Li-ion battery packs (18 V / 4 Ah)
- + 1 tool case (L-BOXX 136)
- + 1 allen key 2 mm
- + 1 hand guard
- + 1 roll painter's tape (32133038000)
- + 1 rapid charger BC 1880 CV AS (92604335010)

Product feature

- + Reversing blade
- + Hand guard
- + Variable speed

Application

Curve cuts

++

Coil cuts

++

Inside cutouts

+

Notches

+

+ suitable
++ well suitable

Technical data

TECHNICAL DATA

Battery voltage	18 V
Battery capacity	4 Ah
Battery compatibility	Li-ion / CORE 18 V Li-ions
Battery interface	18 V AMPShare
Strokes	2 200 - 3 500 spm
Cutting speed	19.7 [6] - 29.5 [9] ft/min[m/min]
Steel 58,000 lbf/in ²	1/16 [1.6] in[mm]
Steel 87,000 lbf/in ²	3/64 [1.2] in[mm]
Steel 116,000 lbf/in ²	3/64 [1] in[mm]
Non-ferrous metals up to 36,000 lbf/in ²	3/32 [2] in[mm]
Radius of smallest curve	1/2 [15] in[mm]
Weight without battery	3.17 [1.44] lbs[kg]

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA
Measurement uncertainty of the measured value KpA

74,2 dB
3 dB

Sound power level LWA
Measurement uncertainty of the measured value KWA

85,2 dB
3 dB

Peak sound value
LpCpeak
Measurement uncertainty of the measured value KpCpeak

86,0 dB
3 dB

Vibration value 1 α_{hv} 3-way
Measurement uncertainty of the measured value K α

ah 5,2 m/s²
1,5 m/s²

Application examples

