



ASB 18 Q AS

2-speed cordless combi drill

With brushless motor and QuickIN interface. Perfectly suited to drilling up to 13 mm in metal, stone and masonry.

Product number: 7 104 07 61 00 0

Details

- + 2-speed solid metal gearbox and switchable striking mechanism for optimum drilling in metal, stone and masonry.
- + Enjoy the greatest versatility with the FEIN QuickIN system. Work at speed in metal and timber with just one tool.
- + QuickIN solid metal drill chuck (120 Nm) with carbide-tipped clamping jaws and high clamping forces.
- + Brushless FEIN PowerDrive motor with 30 % higher efficiency and long service life.
- + Mechanical torque setting.
- + Compact design.
- + The AMPShare interface makes almost 50% more screw connections (approx. 1300 screw connections, diameter of 5 x 40 mm in timber) possible per battery charge with the same level of FEIN quality. (ProCORE 4 Ah).
- + Bit and belt holder on the side for ergonomic and flexible handling.
- + Compatible with all 18 V AMPShare ProCORE batteries and chargers for even more power and flexibility. Also suitable for 18 V Bosch Professional cordless devices.
- + Compatible with Bosch Professional 18 V batteries (available since 2008) and AMPShare batteries.
- + Maximum work progress with AMPShare 18V ProCORE batteries: COOLPACK 2.0 technology delivers a 135% longer battery life. State-of-the-art cell technology and intelligent battery management deliver 87% more power than with conventional batteries. "Electronic Cell Protection" (ECP) protects the battery from overload, overheating and total discharge.
- + Ideally equipped for every form of use. Mobile working with the L-BOXX system.

Price includes

- + 1 QuickIN drill chuck (120 Nm)
- + 1 magnetic bit storage
- + 1 belt clip
- + 1 tool case (L-Boxx 136)

Product feature

- + Removable drill chuck
- + QuickIN accessory interface
- + Switchable impact mechanism

Technical data



TECHNICAL DATA

Battery voltage	18 V
Battery compatibility	Li-ion / ProCORE Li-ion
Battery interface	18 V AMPShare
Motor	brushless
Gearbox	2-speed
Accessory interface	QuickIN
Speed, no load	450 / 2,000 rpm
Impacts	7,360 / 32,000 rpm
Max. torque (hard/soft)	60 / 38 Nm
Torque levels	22 + 1
Drill chuck clamping width	1.5 - 13 mm
Fastening	8 x 300 mm
Capacity in steel Ø	13 mm
Capacity in wood Ø	50 mm
Capacity in stone Ø	13 mm
Tapping	M 10
Weight without storage battery	1.50 kg

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA
Uncertainty of measured value
KpA

92,9 dB
3 dB

Sound power level LWA
Uncertainty of measured value
KWA

100,9 dB
3 dB

Sound peak value
LpCpeak
Uncertainty of measured value
KpCpeak

110,0 dB
3 dB

Vibration value 1 α_{hv} 3-way
Vibration value 2 α_{hv} 3-way

ah,D 1,4 m/s²
ah 0,6 m/s²

Uncertainty of measured
value K α

1,5 m/s²

Application examples



FEIN



Powered by



BOSCH

**Kompatibel mit
AMPShare-/ Bosch
Professional 18 V
Akkus. | Compatible
with AMPShare/Bosch**

Professional 18 V batteries. | Compatible avec
les batteries 18 V AMPShare/Bosch Professional. |
Compatible con baterías AMPShare/Bosch
Professional de 18 V. | Compatibile con le batterie
AMPShare / Bosch Professional da 18 V.

