



ASCD 18-1000 W34 AS

Cordless impact wrench/driver

Up to max. 1050 Nm with brushless motor and 6-stage torque setting. For metric screwdriving applications up to M27.

Product number: 7 115 12 61 00 0

Details

- + For extreme precision work: The ASCD 18-1000 W34 AS with electronic torque setting (6 levels) prevents screw heads from shearing off.
- + VARIO 3/4" adapter, available as an extra and developed by FEIN. Suitable for all VARIO accessories for simple and mechanical drilling, countersinking, tapping, recutting and cleaning through threads up to a maximum of M30. Turns the impact wrench/driver into a tapper, thereby adding a whole new tool to the range of applications.
- + Brushless FEIN PowerDrive motor with 30 % higher efficiency and long service life.
- + 3/4" square head for holding sockets.
- + High torque of up to 1050 Nm for tightening and loosening screws of up to M27.
- + Maximum release torque of 1500 Nm in reverse running.
- + Robust solid metal impact gear.
- + Up to 600 screw connections (M27) with one battery charge (ProCORE 8.0 Ah).
- + Compatible with Bosch Professional 18 V batteries (available since 2008) and AMPShare batteries.
- + Maximum work progress with AMPShare 18V ProCORE batteries: COOLPACK 2.0 technology delivers a 135% longer battery life. State-of-the-art cell technology and intelligent battery management deliver 87% more power than with conventional batteries. "Electronic Cell Protection" (ECP) protects the battery from overload, overheating and total discharge.
- + Ideally equipped for every job. Mobile working with the L-BOXX system.

Price includes

- + 1 tool case (L-BOXX 136)

Technical data

TECHNICAL DATA

Battery voltage

18 V

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA
Uncertainty of measured value
KpA

96,7 dB
3 dB



Battery compatibility	Li-ion / ProCORE Li-ion	Sound power level LWA Uncertainty of measured value KWA	104,7 dB 3 dB
Battery interface	18 V AMPShare	Sound peak value LpCpeak Uncertainty of measured value KpCpeak	121,3 dB 3 dB
Motor	brushless	Vibration value 1 α_{hv} 3- way Uncertainty of measured value K α	ah 15,7 m/s ² 1,5 m/s ²
Speed, no load	0 - 1 800 rpm		
Impacts	0 - 2 200 rpm		
Max. torque	1 050 Nm		
Torque levels	6		
Tool Holder	3/4 in Outer square		
Max. metric screw	M27 (8.8)		
Wood screw \emptyset	12 x 600 mm		
Weight without storage battery	3.10 kg		

Application examples



**Kompatibel mit
AMPShare-/ Bosch
Professional 18 V
Akkus.** | Compatible
with AMPShare/Bosch

Professional 18 V batteries. | Compatible avec
les batteries 18 V AMPShare/Bosch Professional. |
Compatible con baterias AMPShare/Bosch
Professional de 18 V. | Compatibile con le batterie
AMPShare / Bosch Professional da 18 V.





FEIN

