



ABH 18-26 AS

Cordless rotary hammer drill

With SDS plus and an impact energy of 2.6 joules for drilling up to 26 mm in concrete.

Product number: 7 140 03 61 00 0

Details

- + The powerful, brushless motor delivers 2.6 joules of impact energy and ensures rapid drilling progress as well as high chisel grinding capacity.
- + Kickback monitoring with intelligent rapid shutdown should the hammer drill kick back suddenly for optimum user protection.
- + Electronic Precision Control (EPC) slowly ramps up the working speed for perfect handling and control when working with sensitive materials and challenging surfaces.
- + Simple and precise speed control using the throttle.
- + Fatigue-free working thanks to compact design and few vibrations.
- + Change the chisel position (Vario-Lock) – lock the chisel in 36 positions for the optimum working position every time.
- + Bright working area thanks to integrated LED light.
- + Clamps or hooks the bit if the drive to the drill spindle is interrupted.
- + Compatible with Bosch Professional 18 V batteries (available since 2008) and AMPShare batteries.
- + Maximum work progress with AMPShare 18V ProCORE batteries: COOLPACK 2.0 technology delivers a 135% longer battery life. State-of-the-art cell technology and intelligent battery management deliver 87% more power than with conventional batteries. “Electronic Cell Protection” (ECP) protects the battery from overload, overheating and total discharge.
- + ProCORE Li-Ion battery with high-power cells, charge status indicator and “Electronic Cell Protection” (ECP). ECP protects against overload, overheating and total discharge.
- + Ideally equipped for every form of use. Mobile working with the L-BOXX system.

Price includes

- + 1 handle
- + 1 x tool cloth
- + 1 depth stop
- + 1 tool case (L-Boxx 136)

Technical data

TECHNICAL DATA

VIBRATION AND SOUND EMISSION VALUES



Battery voltage	18 V	Sound pressure level LpA Uncertainty of measured value KpA	88 dB 3 dB
Battery compatibility	Li-ion / ProCORE Li-ion		
Battery interface	18 V AMPShare	Sound power level LWA Uncertainty of measured value KWA	99 dB 3 dB
Motor	brushless	Vibration value 1 α_{hv} 3-way	$\alpha_{h,D}$ 15,2 m/s ²
Speed, no load	0 - 980 rpm	Vibration value 2 α_{hv} 3-way	$\alpha_{h,D}$ 9,9 m/s ²
Impacts	0 - 4,350 rpm	Uncertainty of measured value K α	1,5 m/s ²
Impact energy	2.6 J		
Tool Holder	SDS-plus		
Hole diameter, concrete	26 mm		
Hole diameter, masonry	68 mm		
Capacity in steel Ø	13 mm		
Capacity in wood Ø	30 mm		
Weight without storage battery	3.20 kg		

Application examples



FEIN



Powered by



BOSCH

**Kompatibel mit
AMPSHARE-/ Bosch
Professional 18 V
Akkus. | Compatible
with AMPSHARE/Bosch**

Professional 18 V batteries. | Compatible avec
les batteries 18 V AMPSHARE/Bosch Professional. |
Compatible con baterías AMPSHARE/Bosch
Professional de 18 V. | Compatibile con le batterie
AMPSHARE / Bosch Professional da 18 V.

