



GSZ 4-280 EL

Straight grinder 28 000/min

Extremely ergonomic die grinder with high plunge depth for light grinding and deburring in especially difficult-toreach spots.

Product number: 7 223 24 60 00 0

Details

- + Long narrow neck and maximum diameter of 210 mm allows tool to plunge a long way into workpieces (e.g. grinding inside pipes).
- + Innovative collets with all-round flange to protect the workpiece and prevent the wrench sliding off

during tool changes.

- + Variable speed allows different tools to be used.
- → Motor and electronics protected against metal dust.
- + Removable rubber collar bearing cover.

Price includes

- + 1 collet Ø 6 mm
- + Jaw spanner SW17

Product feature

+ Long neck

Application

+ Jaw spanner SW13



VALUES

VIBRATION AND SOUND EMISSION

Cutting

Roughing-down

Grinding

Deburring

Brushing

+ suitable
+ well suitable

Technical data

TECHNICAL DATA

Input	350 W	Sound pressure level LpA Uncertainty of measured value KpA	83 dB 3 dB
Output	170 W		
Speed, no load	13,000 - 28,000 rpm	Sound power level LWA Uncertainty of measured value KWA	94 dB 3 dB
Grinding wheel for max. Ø	20 mm	Sound peak value LpCpeak	95 dB
Collet for max. Ø	6 mm	Uncertainty of measured value KpCpeak	3 dB
Collar Ø	43 mm	Vibration value 1 αhv 3-	4,8 m/s²
Max. cutter diameter	12 mm	Way Uncertainty of measured value Κα	1,5 m/s²
Cable with plug	5 m		
Weight according to EPTA	1.50 kg		

Application examples



