



GSZ 8-90 PEL

Straight Grinder, 9 000/min

Ergonomic, powerful die grinder for stainless steel processing with high plunge depth for grinding and polishing in especially difficult-to-reach spots.

Product number: 7 223 20 60 24 1

Details

- + Long narrow neck allows tool to plunge a long way into workpieces (e.g. grinding inside pipes).
- + User protection features include blockage monitoring, restart protection, soft start and electronic overload protection.
- Innovative collets with all-round flange to protect the workpiece and prevent the wrench sliding off during tool changes.
- + POWERtronic tachoelectronics for enormous power, power reserve and exceptional speed stability under load.
- + Removable rubber collar bearing cover.
- + Motor and electronics protected against metal dust.
- + Variable speed allows different tools to be used.

Price includes

- + 1 collet Ø 6 mm
- + Jaw spanner SW17

+ Jaw spanner SW13

Product feature

+ Long neck

Application



Grinding Brushing Satin-finishing Polishing + suitable

VALUES

++ well suitable

VIBRATION AND SOUND EMISSION

Technical data

Weight according to

EPTA

1.80 kg

TECHNICAL DATA

710 W Input Sound pressure level LpA 84 dB Uncertainty of measured value 3 dB KpA 410 W Output 95 dB Sound power level LWA 2,500 - 9,000 rpm Speed, no load Uncertainty of measured value 3 dB 50 mm Grinding wheel for max. 97 dB Sound peak value Ø LpCpeak 3 dB Uncertainty of measured value Collet for max. Ø 8 mm **KpCpeak** Collar Ø 43 mm Vibration value 1 α hv 3-1,9 m/s² way Vibration value 2 α hv 3-way 2,9 m/s² Max. cutter diameter 12 mm Uncertainty of measured 1,5 m/s² Cable with plug 4 m value Kα