



# MULTIMASTER MM 700 1.7 Q Bus & Truck

## Oscillating multi-tool – MM 700

Our best oscillating MultiMaster including an extensive set of accessories for work on cars and commercial vehicles.

Product number: 7 229 70 64 24 0

### Details

- + Anti-vibration system: continuously safe and pleasant working thanks to minimal vibrations and outstanding noise insulation.
- + QuickIN: tool changes in less than 3 seconds thanks to the patented tool-free FEIN rapid clamping system.
- + Hexagonal tool holder for optimum torque transfer.
- + 450 W FEIN high-power motor: high-power motor with a high copper content, which is suited to continuous use and overload for maximum cutting speed and the most rapid work progress.
- + Tacho generator: constant speeds even under load and infinitely variable electronic speed control.
- + Metal gearbox: ability to withstand high loading and outstanding service life because all the gearbox parts are made from metal.
- + Industrial cable: large working radius thanks to finely stranded 5 metre rubber cable of industrial quality.
- + Ideally equipped for every job. Mobile working with the L-BOXX system.

### Price includes

- + 1 Hook-shaped cutter blade, toothed (form 217)
- + 1 Spade-shaped scraper knife, with scratch-protective coating (form 105)
- + 2 L-shaped cutter blades, toothed (form 207)
- + 2 Straight cutter blades, toothed (form 073)
- + 1 Straight cutter blades, curved shape, Z-bend (form 072)
- + 1 U-shaped cutter blade, toothed (form 212)
- + 2 straight cutter blades, Z-bend, toothed (form 081)
- + 1 L-shaped cutter blade, toothed (form 209)
- + 1 protective cover for tool changes
- + 1 traction cable with fastening
- + 1 sharpening stone (63719010014)
- + 1 tool case (L-BOXX 136)

### Technical data

## TECHNICAL DATA

|                          |                     |
|--------------------------|---------------------|
| Input                    | 450 W               |
| Output                   | 250 W               |
| Oscillations             | 10,000 - 19,500 rpm |
| Tool Holder              | 12-sided            |
| Tool change              | QuickIN             |
| Amplitude                | 2 x 1,7°            |
| Cable with plug          | 5 m                 |
| Weight according to EPTA | 1.65 kg             |
| Weight according to EPTA | 1.65 kg             |

## VIBRATION AND SOUND EMISSION VALUES

|   |                 |
|---|-----------------|
| Sound pressure level LpA<br>Uncertainty of measured value<br>KpA        | 85,0 dB<br>3 dB |
| Sound power level LWA<br>Uncertainty of measured value<br>KWA           | 96,0 dB<br>3 dB |
| Sound peak value<br>LpCpeak<br>Uncertainty of measured value<br>KpCpeak | 97,0 dB<br>3 dB |

## Application examples

