



MULTIMASTER AMM 700 1.7 Q Joint Renovation

Battery-powered oscillating multi-tool

Our best MultiTool specially for grouting renewal with durable 12-star receptacle and 7 blades for cutting out elastic joints.

Product number: 7 129 37 64 00 0

Details

- + Precision – MultiTools get into hard-to-reach places. Thanks to vibration damping, they work quietly and precisely.
- + Versatility – blade lengths up to 98 mm allow even very deep joints to be cut. The diamond-coated cleaning blade cleans mortar flanks before you fill them in again.
- + Safety and simplicity – MultiTools work precisely and safely in the joint. Blades don't break and the power tool is protected against overload and overheating. Misuse is almost impossible.
- + Anti-vibration system: continuously safe and pleasant working thanks to minimal vibrations and outstanding noise insulation.
- + QuickIN: tool changes in less than 3 seconds thanks to the patented tool-free FEIN rapid clamping system.
- + 12-sided holder for optimum torque transfer.
- + 18 V FEIN PowerDrive motor: very powerful and virtually wear-free, brushless motor offering great efficiency, ability to handle extreme loads and a long service life.
- + Tacho generator: constant speeds even under load and infinitely variable electronic speed control.
- + Metal gearbox: ability to withstand high loading and outstanding service life because all the gearbox parts are made from metal.
- + Electronic Cell Protection (ECP): ECP protects against overload, overheating and total discharge.
- + The COOLPACK technology ensures a longer battery life and therefore makes long operating periods possible.
- + The battery charge can be read off the battery.
- + Compatible with AMPShare/Bosch Professional 18 V batteries.
- + Ideally equipped for every job. Mobile working with the L-BOXX system.

Price includes

- + 5 Cutter blades, straight (form 117) 6 390 31 17 01 5
- + 1 Cutter blade, mushroom shaped 6 390 31 28 01 2
- + 1 protective cover for tool changes
- + 1 plastic tool case (L-BOXX 238)
- + 1 Cutter blade, straight, long (form 116) 6 390 31 16 01 1
- + 1 handle
- + 1 sharpening stone (63719010014)

Technical data

TECHNICAL DATA

Battery voltage

18 V

Battery compatibility

Li-ion / ProCORE Li-ion

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA
Uncertainty of measured value
KpA

77,0 dB
3,0 dB



FEIN

Battery interface	18 V AMPShare	Sound power level LWA Uncertainty of measured value KWA	85,0 dB 3,0 dB
Oscillations	10,000 - 19,500 rpm	Sound peak value LpCpeak Uncertainty of measured value KpCpeak	90,3 dB 3,0 dB
Tool Holder	12-sided	Uncertainty of measured value K α	1,5 m/s ²
Tool change	QuickIN		
Amplitude	2 x 1,7°		
Weight without storage battery	1.10 kg		

Application examples

