



# MULTIMASTER MM 700

## Max Top

### Oscillating multi-tool - MM 700

Our best MultiTool for the most rapid work progress in interior work and renovation with 60 accessories – from sawing in wood, metal and plastics, to cutting out tiles, cutting silicone joints and carpets, removing adhesive residues and tile adhesive.

Product number: 7 229 68 64 24 1

## Details

- + Anti-vibration system: continuously safe and pleasant working thanks to minimal vibrations and outstanding noise insulation.
- + StarlockMax tool mounting: more work progress and greater precision thanks to 100% power transmission without losses.
- + QuickIN: tool changes in less than 3 seconds thanks to the patented tool-free FEIN rapid clamping system.
- + With the StarlockMax tool mounting, you can access around 180 FEIN accessories from the Starlock, Starlock Plus and StarlockMax performance classes.
- + 450 W FEIN high-power motor: high-power motor with a high copper content, which is suited to continuous use and overload for maximum cutting speed and the most rapid work progress.
- + Tacho generator: constant speeds even under load and infinitely variable electronic speed control.
- + Metal gearbox: ability to withstand high loading and outstanding service life because all the gearbox parts are made from metal.
- + Mechanical interface: for stationary operation in the table or drill jig holder or for securing the depth stop.
- + Industrial cable: large working radius thanks to finely stranded 5 metre rubber cable of industrial quality.
- + Electronic safety cut-off – user protection should the saw blade lock, for example.
- + Ideally equipped for every job. Mobile working with the L-BOXX system.

## Price includes

- |   |  |
|---|--|
| + 2 E-Cut standard saw blades curved (35 mm)                    | + 2 E-Cut standard saw blades curved (65 mm)       |
| + 1 E-Cut Precision BIM saw blade (35 mm)                       | + 1 E-Cut Precision BIM saw blade (65 mm)          |
| + 1 E-Cut long-life saw blade (10 mm)                           | + 2 E-Cut long-life saw blades (35 mm)             |
| + 1 E-Cut long-life saw blade (32 mm)                           | + 1 E-Cut long-life saw blade (42 mm)              |
| + 1 E-Cut carbide Pro saw blade (32 mm)                         | + 1 segmented saw blade (Ø 85 mm)                  |
| + 1 carbide saw blade (diameter 75 mm)                          | + 1 HM rasp (triangular)                           |
| + 1 Stopper knife   | + 1 Cutter blade, mushroom shaped 6 390 31 28 01 2 |
| + 1 Multi-function knife  | + 1 Sanding plate with holes                       |
| + Sanding sheets, perforated (10 each of grit 60, 80, 120, 180) | + 1 dust extraction device                         |
| + 1 tool case (L-Boxx 136)                                      |  |

## Product feature

+ Mechanical interface

## Technical data

### TECHNICAL DATA

Input	450 W
Output	250 W
Oscillations	10,000 - 19,500 rpm
Tool Holder	StarlockMax
Tool change	QuickIN
Amplitude	2 x 2,0°
Cable with plug	5 m
Weight according to EPTA	1.60 kg
Weight according to EPTA	1.60 kg

### VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA Uncertainty of measured value KpA	85 dB 3 dB
Sound power level LWA Uncertainty of measured value KWA	96 dB 3 dB
Sound peak value LpCpeak Uncertainty of measured value KpCpeak	97 dB 3 dB

## Application examples

