



BLK 2.0 E

Nibbler up to 2 mm

Compact nibbler with unlimited curve precision for corners and edges.

Product number: 7 232 40 60 24 0

Details

- + High curve precision due to special cutting head geometry. Nibbler can turn on the spot.
- + Especially well-suited for cutting edged sheet metals with a minimum bend radius of 3 mm.
- + Cutting direction setting can be changed in 45° steps up to 360° using tool-free pivoting cutting head.
- + QuickIN clamping system.

- + Optimal ergonomics.
- Motor with outstanding performance and stability.
- + Ideal for cut-outs.
- + Optimally suited for template cuts.
- + Chip protection mesh on vent slots.
- + 5 metre cable.
- + Stainless steel up to 1.0 mm.

Price includes

+ 1 die (3 13 09 040 00 2)

+ 1 punch (6 36 02 051 00 9)

Product feature

- + Cutting direction
- + Adjustable stroke

+ QuickIN

Application



Curve cuts

Interior cut-outs

Profile sections

Notches

Technical data

TECHNICAL DATA

350 W Input 210 W Output Strokes 500 - 1,000 rpm 1 m/min Cutting speed Steel up to 400 N/mm² 2 mm 1.5 mm Steel up to 600 N/mm² Steel up to 800 N/mm² 1 mm 2.5 mm Non-ferrous metals up to 250 N/mm² Cutting width 8 mm Immersion Ø with die 18 mm Rad. of smallest curve 4 / 0 mm (inside/outside) 5 m Cable with plug 1.80 kg

++
++
++
++
+ suitable

++ well suitable

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA Uncertainty of measured value KpA

Sound power level LWA Uncertainty of measured value

Sound peak value LpCpeak Uncertainty of measured value KpCpeak

Vibration value 1 α hv 3-way Uncertainty of measured value $K\alpha$

80 dB 3 dB

91 dB 3 dB

91 dB

3 dB

 7.3 m/s^2

1,5 m/s²



Weight according to EPTA

Application examples



