



ASCD 18-300 W2 AS

Cordless impact wrench/driver

Up to max. 290 Nm with brushless motor and 6-stage torque setting. For metric screwdriving applications up to M18.

Product number: 7 115 10 61 00 0

Details

- + For extreme precision work: The ASCD 18-300 W2 AS with electronic torque setting (6 levels) prevents screw heads from shearing off.
- + VARIO 1/2" adapter, available as an extra and developed by FEIN, suitable for all VARIO accessories for simple and mechanical drilling, countersinking, tapping, recutting and cleaning of through holes up to a maximum of M18. Turns the impact wrench/driver into a tapper, thereby adding a whole new tool to the range of applications.
- + Brushless FEIN PowerDrive motor with 30 % higher efficiency and long service life.
- + 1/2" square for holding sockets.
- + Metric screws up to M18 (8.8).
- + 10% more torque in reverse running to loosen screws which are extremely tight.
- + Robust solid metal impact gear.
- + Contact guard on gearbox head.
- + Up to 600 screw connections (M18) with one battery charge (ProCORE 4 Ah).
- + Compact design.
- + Bit and belt holder on the side for ergonomic and flexible handling.
- + Compatible with Bosch Professional 18 V batteries (available since 2008) and AMPShare batteries.
- + Maximum work progress with AMPShare 18V ProCORE batteries: COOLPACK 2.0 technology delivers a 135% longer battery life. State-of-the-art cell technology and intelligent battery management deliver 87% more power than with conventional batteries. "Electronic Cell Protection" (ECP) protects the battery from overload, overheating and total discharge.
- + Ideally equipped for every form of use. Mobile working with the L-BOXX system.

Price includes

- + 1 belt clip
- + 1 magnetic bit storage
- + 1 tool case (L-Boxx 136)

Technical data

TECHNICAL DATA

VIBRATION AND SOUND EMISSION VALUES

Battery voltage	18 V	Sound pressure level LpA Uncertainty of measured value KpA	99,2 dB 3 dB
Battery compatibility	Li-ion / ProCORE Li-ion		
Battery interface	18 V AMPShare	Sound power level LWA Uncertainty of measured value KWA	107,2 dB 3 dB
Motor	brushless		
Speed, no load	0 - 1700 rpm	Sound peak value LpCpeak Uncertainty of measured value KpCpeak	121,5 dB 3 dB
Impacts	0 - 3400 rpm		
Max. torque	290 Nm	Vibration value 1 α_{hv} 3- way Uncertainty of measured value $K\alpha$	α_h 15,0 m/s ² 1,5 m/s ²
Torque levels	6		
Tool Holder	1/2" Outer square		
Max. metric screw	M18 (8.8)		
Wood screw Ø	8 x 300 mm		
Weight without storage battery	1.20 kg		

Application examples



Kompatibel mit AMPShare- / Bosch Professional 18 V Akkus. | Compatible with AMPShare/Bosch

Professional 18 V batteries. | Compatible avec les batteries 18 V AMPShare/Bosch Professional. | Compatible con baterías AMPShare/Bosch Professional de 18 V. | Compatibile con le batterie AMPShare / Bosch Professional da 18 V.



