



SCT 5-40 X

Dry wall screw gun, up to 5 mm

The specialist tool for drywall and interior work with quiet clutch.

Product number: 7 213 13 24 23 0

Details

- + Speed-optimised; for rapid fixing of plasterboard to wood or metal frames.
- + Silent FEIN CLIC-STOP clutch for working in offices, hospitals etc. without causing a disturbance.
- + The depth stop supplied means that drywall is not damaged and you need simply grout after screwdriving.
- + One of the lightest screwdrivers in its class.
- + Market-leading ergonomics with FEIN Sensitive handle.
- + Point placement accuracy with infinitely variable electronic speed setting.
- + FEIN high-power motor.
- + Vibration-free stop.
- + Rapid changeover to collated strips.
- + Easily adjustable and replaceable depth stop.
- + Dustproof stop sleeve.
- + Extremely lightweight.
- + Practical hand strap.

Price includes

- + 1 hand strap
- + 1 depth stop, dust-proof protection
- + 1 bit ¼" for cross-slotted screws size 2 / Phillips (form H) with dust-protection ring
- + 1 belt clip
- + 1 magnetic holder for bits ¼"

Technical data

TECHNICAL DATA

Input

450 W

Output

250 W

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA
Uncertainty of measured value
KpA

81 dB
3 dB



FEIN

Speed, full load	0 - 2,700 rpm	Sound power level LWA	92 dB
		Uncertainty of measured value	3 dB
Speed, no load	0 - 4,000 rpm		
Max. torque (hard/soft)	12 / - Nm	Sound peak value	98 dB
		LpCpeak	
Screw Ø	5 mm	Uncertainty of measured value	3 dB
		KpCpeak	
Rapid change chuck	1/4 in	Vibration value 1 α_{hv} 3-way	0,8 m/s ²
		Uncertainty of measured value	
Cable with plug	5 m	K α	1,5 m/s ²
Weight according to EPTA	1.30 kg		

Application examples

