



GSZ 4-90 EL

Straight Grinder, 8 500/min

Extremely ergonomic die grinder for stainless steel processing with high plunge depth for light grinding and polishing in especially difficult-to-reach spots.

Product number: 7 223 25 60 00 0

Details

- Long narrow neck and maximum diameter of 210 mm allows tool to plunge a long way into workpieces (e.g. grinding inside pipes).
- Innovative collets with all-round flange to protect the workpiece and prevent the wrench sliding off

during tool changes.

- + Variable speed allows different tools to be used.
- → Motor and electronics protected against metal dust.
- + Removable rubber collar bearing cover.

Price includes

- + Jaw spanner SW17
- + Jaw spanner SW13

+ 1 collet Ø 6 mm

Product feature

+ Long neck

Application



Roughing-down

Brushing

Satin-finishing

Polishing

++

+ suitable
++ well suitable

VALUES

VIBRATION AND SOUND EMISSION

Technical data

TECHNICAL DATA

Input	350 W	Sound pressure level LpA Uncertainty of measured value	83 dB 3 dB
Output	170 W	КрА	
Speed, no load	3,500 - 8,500 rpm	Sound power level LWA Uncertainty of measured value KWA	94 dB 3 dB
Polishing disc Ø	50 mm	Sound peak value	95 dB
Grinding wheel for max. Ø	20 mm	LpCpeak Uncertainty of measured value KpCpeak	3 dB
Collet for max. Ø	6 mm	Vibration value 1 $lpha$ hv 3-	1,0 m/s²
Max. cutter diameter	12 mm	Way Uncertainty of measured value Κα	1,5 m/s²
Cable with plug	5 m		
Weight according to EPTA	1.50 kg		

Application examples



