



VARIO 8.5 mm twist drill (M10 thread)



Long service life, thanks to high material strength (64 HRC), special cutting geometries suited to impact wrench/drivers and a TiAlN (titanium-aluminium-nitride) coating. The bits experience low levels of wear and friction as well as being heat-resistant to 800 °C. Thanks to the high speeds and number of blows, they can therefore be used in steel up to 900 N/mm².|Perfectly suited to the following materials: non-alloyed and alloyed steels up to 900 N/mm², aluminium, brass.

Product number: 6 31 11 043 01 0

Technical data

TECHNICAL DATA

L	90 mm
Spiral length	50 mm
Material	HSS
Coating	Titanium Aluminum Nitride (TiAlN)
Strength	64 HRC
Heat resistance	max. 800°C
Tool Holder	VARIO Bit Shaft
Bore Ø	8.5 mm
Weight	0.04 kg

Suitable for the following tools

- > ASCD 18-300 W2 AS
- > ASCD 18-300 W2 AS Ready to-use Set

- > ASCD 18-300 W2 AS Ready-to-use Set
- > ASCD 18-1000 W34 AS

- > ASCD 18-300 W2 AS Set 5 Ah
- > ASCD 18-1000 W34 AS Set 8 Ah ProCORE

Application examples

