



ABS 18 Q AS

2-speed cordless drill/driver

With brushless motor and QuickIN interface. Perfectly suited to drilling up to 13 mm and tapping up to M10.

Product number: 7 113 24 61 00 0

Details

- + Two-speed solid metal gearbox perfectly suited to drilling up to 13 mm and tapping up to M10 in metal.
- + Enjoy the greatest versatility with the FEIN QuickIN system. Work at speed in metal and timber with just one tool.
- + QuickIN solid metal drill chuck (120 Nm) with carbide-tipped clamping jaws and high clamping forces.
- + Brushless FEIN PowerDrive motor with 30 % higher efficiency and long service life.
- + Mechanical torque setting.
- + Compact design.
- + The AMPShare interface makes almost 50% more screw connections (approx. 1300 screw connections, diameter of 5 x 40 mm in timber) possible per battery charge with the same level of FEIN quality. (ProCORE 4 Ah).
- + Bit and belt holder on the side for ergonomic and flexible handling.
- + Compatible with Bosch Professional 18 V batteries (available since 2008) and AMPShare batteries.
- + Maximum work progress with AMPShare 18V ProCORE batteries: COOLPACK 2.0 technology delivers a 135% longer battery life. State-of-the-art cell technology and intelligent battery management deliver 87% more power than with conventional batteries. "Electronic Cell Protection" (ECP) protects the battery from overload, overheating and total discharge.
- + Ideally equipped for every form of use. Mobile working with the L-BOXX system.

Price includes

- + 1 QuickIN drill chuck (120 Nm)
- + 1 magnetic bit storage
- + 1 belt clip
- + 1 tool case (L-Boxx 136)

Product feature

- + Removable drill chuck
- + QuickIN accessory interface

Technical data

TECHNICAL DATA

VIBRATION AND SOUND EMISSION VALUES



FEIN

Battery voltage	18 V	Sound pressure level LpA Uncertainty of measured value KpA	74,3 dB 5 dB
Battery compatibility	Li-ion / ProCORE Li-ion		
Battery interface	18 V AMPShare	Sound power level LWA Uncertainty of measured value KWA	82,3 dB 5 dB
Motor	brushless	Sound peak value LpCpeak Uncertainty of measured value KpCpeak	88,1 dB 5 dB
Gearbox	2-speed		
Accessory interface	QuickIN		
Speed, no load	450 / 2,000 rpm	Vibration value 1 α_{hv} 3-way Vibration value 2 α_{hv} 3-way	ah,D 1,1 m/s ² ah 1,2 m/s ²
Max. torque (hard/soft)	60 / 38 Nm	Uncertainty of measured value K α	1,5 m/s ²
Torque levels	22 + 1		
Drill chuck clamping width	1.5 - 13 mm		
Fastening	8 x 300 mm		
Capacity in steel Ø	13 mm		
Capacity in wood Ø	50 mm		
Tapping	M 10		
Weight without storage battery	1.40 kg		

Application examples



FEIN



Powered by



BOSCH

**Kompatibel mit
AMPSHARE-/ Bosch
Professional 18 V
Akkus. | Compatible
with AMPSHARE/Bosch**

Professional 18 V batteries. | Compatible avec
les batteries 18 V AMPSHARE/Bosch Professional. |
Compatible con baterías AMPSHARE/Bosch
Professional de 18 V. | Compatibile con le batterie
AMPSHARE / Bosch Professional da 18 V.

