



MBS 32 F

Magnetic Drill Jigs

Flexible magnetic drill jig with fine adjustment for rotary drills with up to 32 mm drill capacity.

Product number: 9 03 16 223 00 8

Details

- + Universal suitability for drilling, tapping, reaming and countersinking.
- + Fine adjustment of drill spindle for easy alignment of machine without constantly removing and refitting the magnet.
- + High magnetic holding power and safety circuit guarantee safe working in any position.
- + Infinitely variable stroke range setting.
- + Compact design.
- + Optimum power-to-weight ratio.
- + Robust and accurate dual dove-tail guide
- + Universal use for drive machines with clamping collar.

Price includes

- + 1 clamping strap
- + 1 Chip grid
- + 1 swarf hook
- + 2 keys

Technical data

TECHNICAL DATA

Input	130 W
Socket max.	16 A
For collar Ø	63 / 65 mm
Twist drill max. Ø	32 mm
Tapping	M 24



Countersinking max. Ø	60 mm
Reaming max. Ø	40 mm
Stroke	178 mm
Total stroke range	365 mm
Adjustment range for drill jigs	10 mm
Swivel range for drill jigs	350°
Magnetic holding power	18,000 N
Magnetic foot dimensions	220 x 100 mm
Cable with plug	4 m
Weight according to EPTA	21.80 kg