

## GWP 10

### Thread drill up to M 10

Fast, accurate thread drill with reversing gear for shorter working times.

Product number: 7 209 38 60 00 0



### Details

- + Unique speed thanks to reversing gear for automatic reversal of rotation direction when retracting drill spindle from threaded hole. Rapid return action at 680 rpm for shorter cycle times.
- + Outstanding precision due to clearance-free connection of drill shaft and threaded chuck with B12 taper mounting for high concentricity. Positive fit of thread drill in chuck for the best results.
- + FEIN sensitive handle for applying feed force in the direct drilling axis while ensuring an ideal position in the guiding hand.
- + FEIN high-power motor with stable speed.
- + Small width across corners of 23 mm.
- + Metal gear head.
- + Distortion-free barrel-type motor housing.

### Price includes

- + 1 additional handle
- + Threaded chuck not included

### Technical data

#### TECHNICAL DATA

|                                 |               |
|---------------------------------|---------------|
| Input                           | 450 W         |
| Output                          | 250 W         |
| Idling speed in reverse running | 0 - 1,000 rpm |
| Load speed when cutting         | 0 - 450 rpm   |
| Load speed in reverse running   | 0 - 680 rpm   |

#### VIBRATION AND SOUND EMISSION VALUES

|   |               |
|---|---------------|
| Sound pressure level LpA<br>Uncertainty of measured value<br>KpA        | 82 dB<br>3 dB |
| Sound power level LWA<br>Uncertainty of measured value<br>KWA           | 93 dB<br>3 dB |
| Sound peak value<br>LpCpeak<br>Uncertainty of measured value<br>KpCpeak | 96 dB<br>3 dB |



# FEIN

|                             |         |   |                      |
|-----------------------------|---------|---|----------------------|
| Torque at max. output power | 21 Nm   | Vibration value 1 $\alpha_{hv}$ 3-way   | 3,0 m/s <sup>2</sup> |
| Stall torque                | 53 Nm   | Uncertainty of measured value $K\alpha$ | 1,5 m/s <sup>2</sup> |
| Thread in steel up to       | M 10    |   |                      |
| Thread in stainless steel   | M 10    |   |                      |
| Cone at drill shaft         | B 12    |   |                      |
| Collar Ø                    | 43 mm   |   |                      |
| Width across corners        | 23 mm   |   |                      |
| Width across corners        | 23 mm   |   |                      |
| Cable with plug             | 5 m     |   |                      |
| Weight according to EPTA    | 1.60 kg |   |                      |

## Application examples



