



## CG 14-125 V

Compact angle grinders, Ø 125 mm

Ergonomic 1400 W compact angle grinder with variable speed for effective grinding and cutting work.

Product number: 7 222 89 60 23 0

### Details

- + Thanks to the powerful 1400 watt motor and a significantly smaller handle (195 mm), faster and more convenient work can be undertaken on the construction site and in metal workshops.
- + New cooling concept with ventilation inlets as well as a removable dust protection filter ensures the tool a longer service life even in extreme conditions.
- + Variable speed settings assist the worker in various working situations.
- + Robust motor for daily use.
- + Long-life thanks to overload protection and long carbon brush service life.
- + Rapid work progress thanks to powerful motor.
- + Gearbox head can be rotated 90° for high versatility.
- + Abrasive materials can be changed at speed and without the need for any tools: quick-clamping nut included in scope of supply as standard.
- + Good ability to cope with overload thanks to direct motor cooling.
- + Cable length 4 m.

### Price includes

- + 1 anti-vibration handle
- + 1 clamping nut
- + 1 two-hole spanner
- + 1 adapter flange
- + 1 wheel guard
- + 1 safety hood for cutter

### Product feature

- + Soft start
- + Blockage monitoring
- + Electronic speed preselection
- + Restart protection
- + Electronic overload protection
- + Kick-back check

### Application

Roughing-down



Deburring



Dividing	+
Brushing	+
Satin-finishing	++
Polishing	++

+ suitable  
++ well suitable

## Technical data

### TECHNICAL DATA

Input	1,400 W
Output	830 W
Speed, no load	2,800 - 11,500 rpm
Grinding disc Ø	125 mm
Elast. Backing pad Ø	125 mm
Flange	M 14
Cable with plug	4 m
Weight according to EPTA	2.30 kg

### VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA Uncertainty of measured value KpA	95 dB 3 dB
Sound power level LWA Uncertainty of measured value KWA	103 dB 3 dB
Sound peak value LpCpeak Uncertainty of measured value KpCpeak	108 dB 3 dB
Vibration value 1 $\alpha_{hv}$ 3-way	4,5 m/s <sup>2</sup>
Vibration value 2 $\alpha_{hv}$ 3-way	2,5 m/s <sup>2</sup>
Uncertainty of measured value K $\alpha$	1,5 m/s <sup>2</sup>

## Application examples



**FEIN**

